

屋内照明器具特性

品番 (品名)	L G W8 1 5 1 3	
光源	LED2700_70_245 ×1	245.0 l m
管理番号	K0142279 (0) DB 1	
B Z 分類	B Z 3	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	50 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	50 %	室指数	照明率 (X0.01)																				Z C M
保守率	良	0.63	0.6	5.4	4.3	3.7	3.2	5.0	4.1	3.5	3.1	4.3	3.6	3.1	2.8	3.7	3.1	2.8	2.5	2.0			
	中	0.6	0.8	6.3	5.3	4.6	4.1	5.8	5.0	4.4	3.9	5.0	4.4	3.9	3.6	4.3	3.8	3.4	3.2	2.5			
	否	0.56	1.0	6.9	6.0	5.3	4.8	6.4	5.6	5.0	4.6	5.5	4.9	4.5	4.1	4.7	4.2	3.9	3.7	2.9			
			1.25	7.4	6.6	6.0	5.5	6.9	6.2	5.6	5.2	5.9	5.4	5.0	4.6	5.0	4.6	4.3	4.1	3.2			
下方投影面積		c m ²	1.5	7.7	7.0	6.4	6.0	7.2	6.6	6.1	5.7	6.2	5.7	5.3	5.0	5.2	4.9	4.6	4.4	3.5			
等価発光面積		c m ²	2.0	8.2	7.6	7.1	6.7	7.6	7.1	6.7	6.3	6.6	6.2	5.9	5.6	5.6	5.3	5.1	4.9	3.8			
取付高さ	器具間隔最大限		2.5	8.5	8.0	7.5	7.2	7.9	7.5	7.1	6.8	6.8	6.5	6.2	6.0	5.8	5.5	5.3	5.2	4.0			
	横方向 (A)	縦方向 (B)	3.0	8.7	8.2	7.9	7.5	8.1	7.7	7.4	7.1	7.0	6.7	6.4	6.2	5.9	5.7	5.5	5.4	4.1			
H m	1.10 H m	1.22 H m	4.0	8.9	8.6	8.3	8.0	8.3	8.0	7.8	7.5	7.2	7.0	6.8	6.6	6.1	5.9	5.8	5.7	4.3			
			5.0	9.1	8.8	8.5	8.3	8.5	8.2	8.0	7.8	7.3	7.1	7.0	6.8	6.2	6.1	5.9	5.8	4.4			
			7.0	9.3	9.1	8.9	8.7	8.7	8.5	8.3	8.1	7.5	7.3	7.2	7.1	6.3	6.2	6.1	6.1	4.6			
			10.0	9.4	9.3	9.1	9.0	8.8	8.7	8.5	8.4	7.6	7.5	7.4	7.3	6.4	6.3	6.3	6.2	4.7			

