

# 屋内照明器具特性

|         |                        |          |
|---------|------------------------|----------|
| 品番 (品名) | L G W 8 5 0 3 0 B K    |          |
| 光源      | LDA5 L - H / E / W × 1 | 485.0 lm |
| 管理番号    | K0162792 ( 0 ) DY 1    |          |
| B Z 分類  | B Z 4                  |          |

|        |                  |          |                  |     |     |      |      |     |     |      |      |     |     |      |      |     |     |      |     |     |       |
|--------|------------------|----------|------------------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|-----|-----|-------|
| 器具効率   | 37 %             | 天井       | 80 %             |     |     |      | 70 % |     |     |      | 50 % |     |     |      | 30 % |     |     |      | 0 % |     |       |
|        | 上方光束             |          | 0 %              | 壁   | 70  | 50   | 30   | 10  | 70  | 50   | 30   | 10  | 70  | 50   | 30   | 10  | 70  | 50   | 30  | 10  | 0 %   |
|        | 下方光束             |          | 37 %             |     | 床   | 10 % |      |     |     | 10 % |      |     |     | 10 % |      |     |     | 10 % |     |     |       |
| 室指数    | 照明率 ( X 0.01 )   |          |                  |     |     |      |      |     |     |      |      |     |     |      |      |     |     |      |     |     | Z C M |
| 保守率    | 良                | 0.63     | 0.6              | 2.2 | 1.7 | 1.5  | 1.3  | 2.1 | 1.7 | 1.5  | 1.3  | 2.0 | 1.7 | 1.4  | 1.3  | 2.0 | 1.6 | 1.4  | 1.3 | 1.2 |       |
|        | 中                | 0.6      | 0.8              | 2.5 | 2.1 | 1.9  | 1.7  | 2.5 | 2.1 | 1.9  | 1.7  | 2.4 | 2.1 | 1.8  | 1.7  | 2.3 | 2.0 | 1.8  | 1.6 | 1.6 |       |
|        | 否                | 0.56     | 1.0              | 2.8 | 2.4 | 2.1  | 1.9  | 2.7 | 2.4 | 2.1  | 1.9  | 2.6 | 2.3 | 2.1  | 1.9  | 2.5 | 2.3 | 2.1  | 1.9 | 1.8 |       |
|        |                  |          | 1.25             | 3.0 | 2.7 | 2.4  | 2.2  | 2.9 | 2.6 | 2.4  | 2.2  | 2.8 | 2.6 | 2.4  | 2.2  | 2.7 | 2.5 | 2.3  | 2.2 | 2.1 |       |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 3.1 | 2.8 | 2.6  | 2.4  | 3.1 | 2.8 | 2.6  | 2.4  | 3.0 | 2.7 | 2.6  | 2.4  | 2.9 | 2.7 | 2.5  | 2.4 | 2.3 |       |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0 | 3.3 | 3.1  | 2.9  | 2.7 | 3.3 | 3.1  | 2.9  | 2.7 | 3.2 | 3.0  | 2.8  | 2.7 | 3.1 | 2.9  | 2.8 | 2.7 | 2.6   |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 3.5 | 3.3 | 3.1  | 2.9  | 3.4 | 3.2 | 3.1  | 2.9  | 3.3 | 3.1 | 3.0  | 2.9  | 3.2 | 3.1 | 2.9  | 2.8 | 2.8 |       |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 3.5 | 3.4 | 3.2  | 3.1  | 3.5 | 3.3 | 3.2  | 3.1  | 3.4 | 3.2 | 3.1  | 3.0  | 3.3 | 3.2 | 3.1  | 3.0 | 2.9 |       |
| H m    | 1.18 H m         | 1.19 H m | 4.0              | 3.7 | 3.5 | 3.4  | 3.3  | 3.6 | 3.5 | 3.4  | 3.2  | 3.5 | 3.4 | 3.3  | 3.2  | 3.4 | 3.3 | 3.2  | 3.2 | 3.1 |       |
|        |                  |          | 5.0              | 3.7 | 3.6 | 3.5  | 3.4  | 3.7 | 3.6 | 3.5  | 3.4  | 3.6 | 3.5 | 3.4  | 3.3  | 3.5 | 3.4 | 3.3  | 3.3 | 3.2 |       |
|        |                  |          | 7.0              | 3.8 | 3.7 | 3.6  | 3.6  | 3.7 | 3.7 | 3.6  | 3.5  | 3.6 | 3.6 | 3.5  | 3.5  | 3.6 | 3.5 | 3.5  | 3.4 | 3.3 |       |
|        |                  |          | 10.0             | 3.8 | 3.8 | 3.7  | 3.7  | 3.8 | 3.7 | 3.7  | 3.6  | 3.7 | 3.7 | 3.6  | 3.6  | 3.6 | 3.5 | 3.5  | 3.4 | 3.4 |       |

