

屋内照明器具特性

品番 (品名)	LRD1210L														
光源	LED2700_70_450 x1 450.0 lm														
管理番号	K0140469(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	4%																			
下方光束	96%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.69 中 0.67 否 0.63	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26	
		0.8	65	54	46	40	64	53	45	40	60	51	44	39	57	49	43	38	36	
		1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43	
		1.25	78	68	60	55	76	67	60	54	72	64	58	53	69	62	57	52	49	
下方投影面積	cm ²	1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	54	
		2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62	
取付高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	74	85	80	76	72	82	78	74	70	67
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	86	82	78	88	83	80	76	84	81	77	74	71
Hm	1.29Hm	1.29Hm	4.0	97	92	88	85	95	91	87	84	91	88	84	82	88	85	82	80	76
			5.0	99	95	92	88	97	93	90	87	93	90	88	85	90	87	85	83	79
			7.0	101	98	96	93	99	97	94	92	96	94	91	89	92	91	89	87	83
			10.0	103	101	99	97	101	99	97	96	98	96	94	93	94	93	92	90	86

