

# 屋内照明器具特性

品番 (品名)	LGC41126											
光源	LED6200_70_4300 x1      4300.0 lm											
管理番号	K0168483 (0) DB1											
BZ分類	BZ5											

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	8 %																			
下方光束	92 %																			
室指数	照明率 ( X0.01)      ZCM																			
保守率	良	0.63	0.6	54	42	34	28	52	41	33	28	49	39	32	27	46	37	31	27	24
	中	0.6	0.8	64	52	44	38	62	51	43	37	58	48	42	37	54	46	40	36	33
	否	0.56	1.0	70	59	51	45	68	58	50	44	64	55	49	43	60	53	47	42	39
			1.25	76	66	58	52	74	64	57	52	70	62	55	50	66	59	53	49	46
下方投影面積	cm <sup>2</sup>		1.5	80	71	64	58	78	69	62	57	73	66	60	56	69	63	58	54	50
等価発光面積	cm <sup>2</sup>		2.0	86	78	72	66	84	76	70	65	79	73	68	63	75	70	65	62	58
取付高さ	器具間隔最大限		2.5	90	83	77	72	87	81	75	71	83	77	73	69	78	74	70	67	62
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	90	84	79	75	85	81	76	73	81	77	74	71	66
H <sub>m</sub>	1.30H <sub>m</sub>	1.30H <sub>m</sub>	4.0	95	90	86	82	93	89	85	81	89	85	81	78	84	81	78	76	71
			5.0	97	93	90	86	95	91	88	85	91	87	85	82	86	84	81	79	75
			7.0	100	97	94	91	98	95	92	89	93	91	89	86	89	87	85	83	79
			10.0	102	99	97	95	99	97	95	93	95	93	92	90	91	90	88	87	82

