

屋内照明器具特性	
品番 (品名)	LGC45801
光源	LED6500_70_4300 x1 4300.0 lm
管理番号	K0157427(0)DB1
BZ分類	BZ5/8.5/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	16%	床	10%				10%				10%				10%				0%	
下方光束	84%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	5.3	4.1	3.3	2.7	5.1	3.9	3.2	2.7	4.7	3.7	3.1	2.6	4.3	3.5	2.9	2.5	2.2
	中	0.6	0.8	6.2	5.0	4.2	3.7	6.0	4.9	4.1	3.6	5.5	4.6	3.9	3.4	5.1	4.3	3.7	3.3	3.0
	否	0.56	1.0	6.9	5.7	4.9	4.3	6.6	5.6	4.8	4.2	6.1	5.2	4.6	4.1	5.6	4.9	4.3	3.9	3.5
			1.25	7.4	6.4	5.6	5.0	7.1	6.2	5.5	4.9	6.6	5.8	5.2	4.7	6.1	5.5	4.9	4.5	4.1
下方投影面積		cm <sup>2</sup>	1.5	7.8	6.9	6.2	5.6	7.5	6.7	6.0	5.4	7.0	6.3	5.7	5.2	6.5	5.9	5.4	5.0	4.5
等価発光面積		cm <sup>2</sup>	2.0	8.4	7.6	6.9	6.4	8.1	7.3	6.7	6.2	7.5	6.9	6.4	5.9	7.0	6.5	6.0	5.7	5.1
取付高さ	器具間隔最大限		2.5	8.7	8.0	7.4	6.9	8.4	7.8	7.2	6.8	7.8	7.3	6.9	6.5	7.3	6.9	6.5	6.1	5.6
	横方向 (A)	縦方向 (B)	3.0	9.0	8.4	7.8	7.4	8.7	8.1	7.6	7.2	8.1	7.6	7.2	6.8	7.5	7.2	6.8	6.5	5.9
1.5m	1.96m	1.96m	4.0	9.3	8.8	8.4	8.0	9.0	8.6	8.1	7.8	8.4	8.0	7.7	7.4	7.9	7.6	7.3	7.0	6.4
2	2.59	2.58	5.0	9.5	9.1	8.7	8.4	9.2	8.8	8.5	8.1	8.6	8.3	8.0	7.7	8.1	7.8	7.6	7.3	6.7
2.5	3.22	3.22	7.0	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	8.9	8.6	8.4	8.2	8.3	8.1	7.9	7.8	7.1
3	3.76	3.76	10.0	10.0	9.7	9.5	9.3	9.7	9.4	9.2	9.0	9.1	8.9	8.7	8.6	8.5	8.4	8.2	8.1	7.4

