

# 屋内照明器具特性

|         |                            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | LGW80307K (WALL)           |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED2700_70_248 x1 248.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0149621(0)DR1             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ9                        |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                                    |          |      |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|------------------------------------|----------|------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%                               | 天井       | 80%  |                 |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |                                    |          | 壁    | 70              | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |
| 上方光束   | 50%                                | 反射率      | 床    | 10%             |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |
| 下方光束   | 50%                                |          | 室指数  | 照明率 (X0.01) ZCM |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良<br>中<br>否<br>0.63<br>0.6<br>0.56 | 0.6      | 4.4  | 3.2             | 2.3 | 1.8 | 4.0 | 2.9 | 2.2 | 1.6 | 3.3 | 2.4 | 1.8 | 1.4 | 2.6 | 1.9 | 1.4 | 1.1 | 0.6 |     |
|        |                                    | 0.8      | 5.2  | 4.0             | 3.2 | 2.5 | 4.8 | 3.7 | 2.9 | 2.3 | 3.9 | 3.0 | 2.4 | 2.0 | 3.1 | 2.4 | 2.0 | 1.6 | 0.9 |     |
|        |                                    | 1.0      | 5.8  | 4.6             | 3.8 | 3.1 | 5.3 | 4.3 | 3.5 | 2.9 | 4.4 | 3.5 | 2.9 | 2.4 | 3.5 | 2.8 | 2.3 | 2.0 | 1.2 |     |
|        |                                    | 1.25     | 6.4  | 5.3             | 4.4 | 3.8 | 5.8 | 4.8 | 4.1 | 3.5 | 4.8 | 4.0 | 3.4 | 2.9 | 3.8 | 3.2 | 2.8 | 2.4 | 1.5 |     |
| 下方投影面積 | c m <sup>2</sup>                   | 1.5      | 6.8  | 5.7             | 4.9 | 4.3 | 6.2 | 5.3 | 4.5 | 4.0 | 5.1 | 4.4 | 3.8 | 3.3 | 4.1 | 3.6 | 3.1 | 2.7 | 1.7 |     |
|        |                                    | 2.0      | 7.4  | 6.4             | 5.7 | 5.1 | 6.7 | 5.9 | 5.3 | 4.7 | 5.6 | 4.9 | 4.4 | 4.0 | 4.5 | 4.0 | 3.6 | 3.3 | 2.1 |     |
| 取付高さ   | 器具間隔最大限                            |          | 2.5  | 7.7             | 6.9 | 6.2 | 5.6 | 7.1 | 6.4 | 5.8 | 5.2 | 5.9 | 5.3 | 4.8 | 4.4 | 4.8 | 4.4 | 4.0 | 3.6 | 2.4 |
|        | 横方向 (A)                            | 縦方向 (B)  | 3.0  | 8.0             | 7.3 | 6.6 | 6.1 | 7.4 | 6.7 | 6.1 | 5.6 | 6.1 | 5.6 | 5.2 | 4.8 | 5.0 | 4.6 | 4.3 | 4.0 | 2.6 |
| H m    | 1.82 H m                           | 1.60 H m | 4.0  | 8.3             | 7.7 | 7.2 | 6.7 | 7.7 | 7.2 | 6.7 | 6.2 | 6.5 | 6.0 | 5.7 | 5.3 | 5.3 | 5.0 | 4.7 | 4.4 | 3.0 |
|        |                                    |          | 5.0  | 8.6             | 8.1 | 7.6 | 7.1 | 7.9 | 7.5 | 7.0 | 6.6 | 6.7 | 6.3 | 6.0 | 5.7 | 5.5 | 5.2 | 5.0 | 4.7 | 3.3 |
|        |                                    |          | 7.0  | 8.9             | 8.4 | 8.1 | 7.7 | 8.2 | 7.8 | 7.5 | 7.2 | 6.9 | 6.6 | 6.4 | 6.1 | 5.7 | 5.5 | 5.3 | 5.1 | 3.6 |
|        |                                    |          | 10.0 | 9.1             | 8.8 | 8.5 | 8.2 | 8.4 | 8.1 | 7.9 | 7.6 | 7.2 | 6.9 | 6.7 | 6.5 | 6.0 | 5.8 | 5.6 | 5.5 | 3.9 |

