

屋内照明器具特性	
品番 (品名)	XF X4 2 0 B S W
光源	LED4000_85_2130 x1 2130.0 lm
管理番号	K0194828(0)DR1
BZ分類	BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	14%	床	10%				10%				10%				10%				0%				
下方光束	86%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	5.2	3.9	3.1	2.5	5.0	3.8	3.0	2.5	4.6	3.6	2.9	2.4	4.2	3.4	2.8	2.3	2.0			
	中	0.77	0.8	6.1	4.9	4.1	3.5	5.9	4.8	4.0	3.4	5.5	4.5	3.8	3.3	5.0	4.2	3.6	3.2	2.8			
	否	0.68	1.0	6.8	5.6	4.8	4.2	6.5	5.5	4.7	4.1	6.0	5.1	4.5	4.0	5.6	4.8	4.3	3.8	3.4			
			1.25	7.4	6.3	5.5	4.9	7.1	6.1	5.4	4.8	6.6	5.8	5.1	4.6	6.1	5.4	4.9	4.4	4.0			
下方投影面積		cm ²	1.5	7.8	6.8	6.0	5.4	7.5	6.6	5.9	5.3	7.0	6.2	5.6	5.1	6.5	5.8	5.3	4.9	4.4			
等価発光面積		cm ²	2.0	8.4	7.5	6.8	6.3	8.1	7.3	6.7	6.1	7.5	6.9	6.3	5.9	7.0	6.5	6.0	5.6	5.1			
取付高さ	器具間隔最大限		2.5	8.7	8.0	7.4	6.8	8.4	7.7	7.2	6.7	7.9	7.3	6.8	6.4	7.3	6.9	6.5	6.1	5.6			
	横方向 (A)	縦方向 (B)	3.0	9.0	8.3	7.8	7.3	8.7	8.1	7.6	7.1	8.1	7.6	7.2	6.8	7.6	7.2	6.8	6.5	5.9			
1.5m	1.64m	2.11m	4.0	9.3	8.8	8.3	7.9	9.0	8.5	8.1	7.7	8.5	8.0	7.7	7.3	7.9	7.6	7.3	7.0	6.4			
2	2.18	2.65	5.0	9.5	9.1	8.7	8.3	9.2	8.8	8.4	8.1	8.7	8.3	8.0	7.7	8.1	7.9	7.6	7.4	6.7			
2.5	2.71	3.21	7.0	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	8.9	8.7	8.4	8.2	8.4	8.2	8.0	7.8	7.2			
3	3.24	3.78	10.0	10.0	9.7	9.5	9.2	9.7	9.4	9.2	9.0	9.1	8.9	8.7	8.6	8.6	8.5	8.3	8.1	7.5			

