

屋内照明器具特性

品番 (品名)	L G W 5 1 7 1 3	
光源	LED2700_70_660 x1	660.0 l m
管理番号	K0150434 (0) DB 1	
B Z 分類	B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	2 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	98 %	室指数	照明率 (X 0 . 0 1)																Z C M	
保守率	良 中 否 0.63 0.6 0.56	0.6	56	44	36	30	55	43	36	30	52	42	35	30	50	41	34	30	28	
		0.8	66	54	46	41	64	53	46	40	61	52	45	40	59	50	44	40	37	
		1.0	73	62	54	48	71	61	53	48	68	59	52	47	65	57	51	47	44	
		1.25	78	69	61	55	77	67	60	55	73	65	59	54	70	64	58	54	51	
下方投影面積	c m ²	1.5	83	74	66	61	81	72	66	60	77	70	64	60	74	68	63	59	56	
		2.0	88	81	74	69	86	79	74	69	83	77	72	68	80	75	70	67	64	
取付高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	74	87	81	77	73	83	79	75	72	69
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	83	78	89	85	81	77	86	82	79	76	73
H m	1.28 H m	1.28 H m	4.0	97	93	89	85	96	91	88	84	92	89	86	83	89	86	84	81	78
			5.0	99	95	92	89	98	94	91	88	94	91	89	86	91	89	87	84	81
			7.0	102	99	96	93	100	97	95	92	97	95	93	91	94	92	90	89	85
			10.0	103	101	99	97	102	100	98	96	99	97	96	94	96	95	93	92	89

