

屋内照明器具特性

品番 (品名)	LSEB1162															
光源	LED6200_70_4500 x1 4500.0 lm															
管理番号	K0150506(0)DB1															
BZ分類	BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	5%	反射率	床	10%				10%				10%				10%				0%
下方光束	95%		室指数	照明率 (X0.01) ZCM																
保守率	良	0.63	0.6	55	43	35	30	54	42	35	30	51	41	34	29	48	39	33	29	27
	中	0.6	0.8	65	54	46	40	63	53	45	40	60	51	44	39	57	49	43	38	36
	否	0.56	1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43
			1.25	78	68	60	54	76	66	59	54	72	64	58	53	69	62	56	52	49
下方投影面積	cm ²		1.5	82	73	66	60	80	71	65	59	76	69	63	58	72	66	61	57	54
等価発光面積	cm ²		2.0	87	80	73	68	85	78	72	68	81	75	70	66	78	73	69	65	61
取付高さ	器具間隔最大限		2.5	91	84	79	74	89	83	78	73	85	80	75	72	81	77	73	70	66
	横方向 (A)	縦方向 (B)	3.0	93	88	83	78	91	86	81	77	88	83	79	76	84	80	77	74	70
Hm	1.26Hm	1.26Hm	4.0	97	92	88	84	95	90	86	83	91	87	84	81	87	84	82	79	75
			5.0	99	95	91	88	97	93	90	87	93	90	87	85	89	87	85	82	79
			7.0	101	98	95	93	99	96	94	91	95	93	91	89	92	90	88	87	83
			10.0	103	101	98	96	101	99	97	95	97	96	94	92	94	93	91	90	86

