

屋内照明器具特性

品番 (品名)	L G W 5 6 9 3 4 B Z														
光源	LDA4L - G - E17 / Z40E / S / W / 2 × 1										440.0 l m				
管理番号	K0138523 (1) DR 1														
B Z 分類	BZ10 / 0.9 / BZ9 / 3.5 / BZ10 / 4.5 / BZ9														

器具効率	74 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	40 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	34 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01) Z C M																	
保守率	良	0.63	0.6	3.2	2.3	1.7	1.3	2.9	2.1	1.5	1.2	2.3	1.7	1.2	9	1.8	1.3	1.0	7	3
	中	0.6	0.8	3.8	2.9	2.3	1.8	3.4	2.6	2.1	1.6	2.8	2.1	1.7	1.3	2.1	1.7	1.3	1.0	5
	否	0.56	1.0	4.2	3.3	2.7	2.2	3.8	3.0	2.5	2.0	3.1	2.5	2.0	1.7	2.4	1.9	1.6	1.3	7
			1.25	4.6	3.8	3.2	2.7	4.2	3.5	2.9	2.5	3.4	2.8	2.4	2.0	2.6	2.2	1.9	1.6	9
下方投影面積	c m ²		1.5	4.9	4.2	3.6	3.1	4.5	3.8	3.3	2.8	3.6	3.1	2.7	2.3	2.8	2.4	2.1	1.8	1.0
等価発光面積	c m ²		2.0	5.4	4.7	4.1	3.7	4.9	4.3	3.8	3.4	4.0	3.5	3.1	2.8	3.1	2.8	2.5	2.2	1.3
取付高さ	器具間隔最大限		2.5	5.6	5.0	4.5	4.1	5.1	4.6	4.1	3.8	4.2	3.8	3.4	3.1	3.3	3.0	2.7	2.5	1.5
	横方向 (A)	縦方向 (B)	3.0	5.8	5.3	4.8	4.4	5.3	4.8	4.4	4.1	4.4	4.0	3.7	3.4	3.5	3.2	2.9	2.7	1.7
H m	0.00 H m	0.00 H m	4.0	6.1	5.6	5.2	4.9	5.6	5.2	4.8	4.5	4.6	4.3	4.0	3.7	3.7	3.4	3.2	3.0	1.9
			5.0	6.3	5.9	5.5	5.2	5.7	5.4	5.1	4.8	4.8	4.5	4.2	4.0	3.8	3.6	3.4	3.2	2.1
			7.0	6.5	6.2	5.9	5.6	5.9	5.7	5.4	5.2	5.0	4.7	4.5	4.3	4.0	3.8	3.7	3.5	2.3
			10.0	6.6	6.4	6.2	6.0	6.1	5.9	5.7	5.5	5.1	4.9	4.8	4.6	4.2	4.0	3.9	3.8	2.5

