

屋内照明器具特性

品番 (品名)	NDNN7 1 5 0 2	
光源	ONU140105LZ9 ×1	1130.0 l m
管理番号	K0132255 (1) DR 1	
B Z 分類	BZ1 / 1.4 / BZ2	

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	79 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	58	52	48	45	58	51	47	45	56	51	47	45	55	50	47	44	43	
	中	0.77	0.8	64	58	54	51	64	58	54	51	62	57	54	51	61	56	53	51	50	
	否	0.68	1.0	68	63	59	56	67	62	59	56	66	61	58	55	64	60	57	55	54	
			1.25	71	67	63	60	71	66	63	60	69	65	62	59	67	64	61	59	58	
下方投影面積	c m ²		1.5	74	69	66	63	73	69	65	63	71	67	65	62	69	66	64	62	60	
	等価発光面積		c m ²	2.0	77	73	70	67	76	72	69	67	74	71	68	66	72	70	68	66	64
取付高さ	器具間隔最大限		2.5	78	75	73	70	77	74	72	70	75	73	71	69	74	72	70	68	67	
	横方向 (A)	縦方向 (B)	3.0	79	77	75	73	79	76	74	72	77	75	73	71	75	73	72	70	69	
H m	1.10 H m	1.10 H m	4.0	81	79	77	75	80	78	76	75	78	77	75	74	76	75	74	73	71	
			5.0	82	80	79	77	81	79	78	77	79	78	77	75	77	76	75	74	72	
			7.0	83	82	81	79	82	81	80	79	80	79	78	77	78	78	77	76	74	
			10.0	84	83	82	81	83	82	81	80	81	80	80	79	79	79	78	78	75	

