

# 屋内照明器具特性

品番 (品名)	NDNN7 1 5 0 2														
光源	NNU141155LZ9 ×1                      1580.0 l m														
管理番号	K0133652 ( 0 ) DR 1														
B Z 分類	BZ1 / 4.5 / BZ2 / 6.0 / BZ1														

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X0.01 )																ZCM		
下方光束	83 %																				
保守率	良 0.81 中 0.77 否 0.68	0.6	64	57	53	50	63	57	53	50	62	56	53	50	60	56	52	50	49		
		0.8	70	64	60	57	69	63	60	57	67	63	59	57	66	62	59	56	55		
		1.0	73	68	64	62	73	68	64	61	71	67	64	61	69	66	63	61	60		
		1.25	77	72	68	66	76	71	68	65	74	70	67	65	72	69	67	65	63		
下方投影面積	c m <sup>2</sup>	1.5	79	74	71	69	78	74	71	68	76	73	70	68	74	71	69	67	66		
		2.0	81	78	75	73	80	77	75	72	79	76	74	72	77	75	73	71	69		
取付高さ	器具間隔最大限		2.5	83	80	78	76	82	79	77	75	80	78	76	74	79	77	75	73	72	
	横方向 (A)	縦方向 (B)	3.0	84	82	80	78	83	81	79	77	81	79	78	76	80	78	77	75	73	
H m	0.78 H m	0.78 H m	4.0	86	84	82	80	85	83	81	80	83	81	80	79	81	80	79	78	76	
			5.0	87	85	83	82	86	84	83	81	84	82	81	80	82	81	80	79	77	
			7.0	88	86	85	84	87	85	84	83	85	84	83	82	83	82	81	81	79	
			10.0	88	87	87	86	87	87	86	85	85	85	84	84	84	83	83	82	80	

