

屋内照明器具特性

品番 (品名)	NDNN7 1 5 0 2	
光源	NUU241105LZ9 ×1	2010.0 lm
管理番号	K0133653 (0) DR 1	
BZ分類	BZ1 / 4.5 / BZ2 / 6.0 / BZ1	

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	83 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	64	57	53	50	63	57	53	50	62	56	53	50	60	56	52	50	49	
	中	0.77	0.8	70	64	60	57	69	63	60	57	67	63	59	57	66	62	59	56	55	
	否	0.68	1.0	73	68	64	62	73	68	64	61	71	67	64	61	69	66	63	61	60	
			1.25	77	72	68	66	76	71	68	65	74	70	67	65	72	69	67	65	63	
下方投影面積	c m ²		1.5	79	74	71	69	78	74	71	68	76	73	70	68	74	71	69	67	66	
	等価発光面積		c m ²	2.0	81	78	75	73	80	77	75	72	79	76	74	72	77	75	73	71	69
取付高さ	器具間隔最大限		2.5	83	80	78	76	82	79	77	75	80	78	76	74	79	77	75	73	72	
	横方向 (A)	縦方向 (B)	3.0	84	82	80	78	83	81	79	77	81	79	78	76	80	78	77	75	73	
H m	0.78 H m	0.78 H m	4.0	86	84	82	80	85	83	81	80	83	81	80	79	81	80	79	78	76	
			5.0	87	85	83	82	86	84	83	81	84	82	81	80	82	81	80	79	77	
			7.0	88	86	85	84	87	85	84	83	85	84	83	82	83	82	81	81	79	
			10.0	88	87	87	86	87	87	86	85	85	85	84	84	84	83	83	82	80	

