

# 屋内照明器具特性

|         |                      |          |
|---------|----------------------|----------|
| 品番 (品名) | HH- XSB0001L         |          |
| 光源      | LED2700_70_470 x1    | 470.0 lm |
| 管理番号    | K0152754 (0) DB1     |          |
| BZ分類    | BZ10/0.7/BZ9/2.3/BZ8 |          |

|                  |                 |         |        |      |     |      |      |      |      |     |     |     |     |     |     |     |     |     |     |     |     |     |
|------------------|-----------------|---------|--------|------|-----|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率             | 90%             | 天井      | 80%    |      |     |      | 70%  |      |      |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |     |
|                  | 上方光束            |         | 54%    | 70   | 50  | 30   | 10   | 70   | 50   | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |     |
|                  | 下方光束            |         | 36%    | 10%  |     |      |      | 10%  |      |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |     |
| 室指数              | 照明率 ( X0.01 )   |         |        |      |     |      |      |      |      |     |     |     |     |     |     |     |     |     |     | ZCM |     |     |
| 保守率              | 良               | 0.63    | 0.6    | 0.56 | 0.6 | 3.9  | 2.8  | 2.1  | 1.6  | 3.5 | 2.5 | 1.9 | 1.5 | 2.8 | 2.0 | 1.5 | 1.2 | 2.1 | 1.5 | 1.1 | 0.9 | 0.3 |
|                  | 中               | 0.6     | 0.6    | 0.56 | 0.6 | 4.6  | 3.6  | 2.8  | 2.3  | 4.2 | 3.2 | 2.6 | 2.1 | 3.3 | 2.6 | 2.0 | 1.7 | 2.5 | 2.0 | 1.6 | 1.3 | 0.6 |
|                  | 否               | 0.56    | 0.6    | 0.56 | 0.6 | 5.2  | 4.1  | 3.4  | 2.8  | 4.6 | 3.7 | 3.1 | 2.6 | 3.7 | 3.0 | 2.5 | 2.1 | 2.8 | 2.3 | 1.9 | 1.6 | 0.8 |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 1.5    | 2.0  | 2.5 | 5.7  | 4.7  | 4.0  | 3.4  | 5.1 | 4.3 | 3.6 | 3.1 | 4.1 | 3.4 | 2.9 | 2.5 | 3.1 | 2.6 | 2.3 | 1.9 | 1.0 |
|                  |                 | 2.0     | 2.5    | 3.0  | 4.0 | 6.0  | 5.1  | 4.4  | 3.9  | 5.4 | 4.7 | 4.1 | 3.6 | 4.3 | 3.8 | 3.3 | 2.9 | 3.3 | 2.9 | 2.5 | 2.2 | 1.2 |
|                  |                 | 2.0     | 2.5    | 3.0  | 4.0 | 6.5  | 5.8  | 5.1  | 4.6  | 5.9 | 5.2 | 4.7 | 4.2 | 4.7 | 4.2 | 3.8 | 3.5 | 3.7 | 3.3 | 3.0 | 2.7 | 1.5 |
| 取付高さ             | 器具間隔最大限         |         | Hm     | Hm   | Hm  | 2.5  | 3.0  | 4.0  | 5.0  | 7.0 | 7.8 | 7.5 | 7.2 | 6.9 | 7.1 | 6.9 | 6.6 | 6.3 | 5.9 | 5.6 | 5.4 | 5.2 |
|                  | 横方向 (A)         | 縦方向 (B) |        |      |     | 3.0  | 4.0  | 5.0  | 7.0  | 7.8 | 7.5 | 7.2 | 6.9 | 7.1 | 6.9 | 6.6 | 6.3 | 5.9 | 5.6 | 5.4 | 5.2 | 4.6 |
| 取付高さ             | Hm              | 0.00Hm  | 0.00Hm |      |     | 4.0  | 5.0  | 7.0  | 10.0 | 7.4 | 6.9 | 6.5 | 6.1 | 6.7 | 6.3 | 5.9 | 5.6 | 5.5 | 5.1 | 4.8 | 4.6 | 4.3 |
|                  |                 |         |        |      |     | 5.0  | 7.0  | 10.0 | 8.0  | 7.6 | 7.2 | 6.8 | 6.4 | 6.9 | 6.5 | 6.2 | 5.9 | 5.6 | 5.4 | 5.1 | 4.9 | 4.5 |
|                  |                 |         |        |      |     | 7.0  | 10.0 | 8.0  | 7.8  | 7.5 | 7.2 | 6.9 | 6.7 | 7.1 | 6.9 | 6.6 | 6.3 | 5.9 | 5.6 | 5.4 | 5.2 | 4.6 |
|                  |                 |         |        |      |     | 10.0 | 8.0  | 7.8  | 7.5  | 7.3 | 7.3 | 7.1 | 6.9 | 6.7 | 6.0 | 5.9 | 5.7 | 5.6 | 4.8 | 4.7 | 4.6 | 4.4 |

