

屋内照明器具特性

品番 (品名)	NDNN74022																
光源	LED4000_80_1790 x1 1790.0 lm																
管理番号	K0137628(0)DB1																
BZ分類	BZ1																

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01) ZCM																
保守率	良	0.76	0.6	85	79	75	73	84	79	75	72	83	78	75	72	82	77	74	72	71
	中	0.72	0.8	91	86	82	80	90	85	82	79	89	84	81	79	87	84	81	79	78
	否	0.64	1.0	94	90	87	84	94	89	86	84	92	88	86	84	91	87	85	83	82
			1.25	97	93	90	88	96	93	90	88	95	92	89	87	93	91	89	87	85
下方投影面積	c m ²		1.5	99	96	93	91	98	95	92	90	96	94	92	90	95	93	91	89	88
			2.0	102	99	96	94	101	98	96	94	99	97	95	93	97	95	94	92	91
取付高さ	器具間隔最大限		2.5	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92
	横方向 (A)	縦方向 (B)	3.0	104	102	100	98	103	101	99	98	101	99	98	97	99	98	97	96	94
H m	1.07 H m	1.07 H m	4.0	105	103	102	101	104	102	101	100	102	101	100	99	100	99	98	97	95
			5.0	106	104	103	102	105	103	102	101	103	102	101	100	101	100	99	98	96
			7.0	107	106	105	104	105	104	104	103	103	103	102	101	101	101	100	100	97
			10.0	107	106	106	105	106	105	105	104	104	104	103	103	102	102	101	101	98

