

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | X F X 2 1 0 M E W            |
| 光源       | LED4000_85_1400 ×1 1400.0 lm |
| 管理番号     | K0193032 ( 0 ) DB 1          |
| B Z 分類   | B Z 4                        |

| 器具効率     |           | 100 %           | 反射率    | 天井   | 80 %                |     |     |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------|-----------------|--------|------|---------------------|-----|-----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|
|          |           |                 |        | 壁    | 70                  | 50  | 30  | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |           |                 |        | 床    | 10 %                |     |     |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |           |                 |        | 室指数  | 照明率 ( X0.01 ) Z C M |     |     |     |      |     |    |     |      |    |    |    |      |    |    |    |     |
| 保守率      |           | 良<br>中<br>否     | 0.81   | 0.6  | 59                  | 47  | 40  | 35  | 58   | 47  | 40 | 34  | 55   | 46 | 39 | 34 | 53   | 45 | 39 | 34 | 32  |
|          |           |                 | 0.77   | 0.8  | 69                  | 58  | 51  | 46  | 68   | 58  | 51 | 46  | 65   | 56 | 50 | 45 | 63   | 55 | 49 | 45 | 43  |
|          |           |                 | 0.68   | 1.0  | 76                  | 66  | 59  | 54  | 75   | 65  | 59 | 53  | 72   | 64 | 58 | 53 | 69   | 62 | 57 | 53 | 51  |
|          |           |                 |        | 1.25 | 82                  | 73  | 66  | 61  | 80   | 72  | 66 | 61  | 78   | 70 | 65 | 60 | 75   | 69 | 64 | 60 | 58  |
| 下方投影面積   |           | cm <sup>2</sup> |        | 1.5  | 86                  | 78  | 72  | 67  | 84   | 77  | 71 | 66  | 82   | 75 | 70 | 66 | 79   | 73 | 69 | 65 | 63  |
|          |           |                 | 等価発光面積 |      | cm <sup>2</sup>     | 2.0 | 91  | 85  | 79   | 75  | 90 | 84  | 79   | 74 | 87 | 82 | 77   | 73 | 84 | 80 | 76  |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5    | 95   | 89                  | 84  | 80  | 93  | 88   | 83  | 80 | 90  | 86   | 82 | 79 | 88 | 84   | 81 | 78 | 75 |     |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0    | 97   | 92                  | 88  | 84  | 95  | 91   | 87  | 83 | 93  | 89   | 85 | 82 | 90 | 87   | 84 | 81 | 79 |     |
| 1.5m     | 1.96 m    | 1.92 m          | 4.0    | 100  | 96                  | 92  | 89  | 98  | 95   | 91  | 89 | 96  | 93   | 90 | 87 | 93 | 90   | 88 | 86 | 83 |     |
| 2        | 2.6       | 2.53            | 5.0    | 101  | 98                  | 95  | 93  | 100 | 97   | 94  | 92 | 97  | 95   | 93 | 90 | 95 | 93   | 91 | 89 | 86 |     |
| 2.5      | 3.25      | 3.14            | 7.0    | 103  | 101                 | 99  | 97  | 102 | 100  | 98  | 96 | 99  | 98   | 96 | 94 | 97 | 95   | 94 | 93 | 90 |     |
| 3        | 3.92      | 3.76            | 10.0   | 105  | 103                 | 102 | 100 | 104 | 102  | 100 | 99 | 101 | 100  | 98 | 97 | 99 | 98   | 97 | 96 | 93 |     |

