

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | X F X 2 0 0 U E W           |
| 光源       | LED4000_85_760 x1 760.0 l m |
| 管理番号     | K0191891 ( 0 ) DB 1         |
| B Z 分類   | B Z 5 / 1.8 / B Z 4         |

| 器具効率   |         | 100 %           | 反射率               | 天井  | 80 %            |     |    |     |     | 70 % |    |     |    |    | 50 % |    |    |    |    | 30 % |     |    |    |  | 0 % |
|--------|---------|-----------------|-------------------|-----|-----------------|-----|----|-----|-----|------|----|-----|----|----|------|----|----|----|----|------|-----|----|----|--|-----|
|        |         |                 |                   | 壁   | 70              | 50  | 30 | 10  | 70  | 50   | 30 | 10  | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 0 % |    |    |  |     |
| 上方光束   |         | 0 %             |                   | 床   | 10 %            |     |    |     |     | 10 % |    |     |    |    | 10 % |    |    |    |    | 10 % |     |    |    |  | 0 % |
| 下方光束   |         | 100 %           | 照明率 ( X0.01 ) ZCM |     |                 |     |    |     |     |      |    |     |    |    |      |    |    |    |    |      |     |    |    |  |     |
| 保守率    |         | 良<br>中<br>否     | 0.81              | 0.6 | 57              | 45  | 37 | 31  | 56  | 44   | 37 | 31  | 53 | 43 | 36   | 31 | 51 | 42 | 36 | 31   | 29  |    |    |  |     |
|        |         |                 | 0.77              | 0.8 | 67              | 56  | 48 | 42  | 66  | 55   | 47 | 42  | 63 | 53 | 47   | 42 | 60 | 52 | 46 | 41   | 39  |    |    |  |     |
|        |         |                 | 0.68              | 1.0 | 74              | 63  | 55 | 50  | 72  | 62   | 55 | 50  | 69 | 61 | 54   | 49 | 67 | 59 | 53 | 49   | 47  |    |    |  |     |
|        |         |                 | 1.25              | 80  | 70              | 63  | 57 | 78  | 69  | 63   | 57 | 75  | 68 | 62 | 57   | 72 | 66 | 61 | 56 | 54   |     |    |    |  |     |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5               | 84  | 75              | 69  | 63 | 82  | 74  | 68   | 63 | 79  | 72 | 67 | 62   | 77 | 71 | 66 | 62 | 59   |     |    |    |  |     |
|        |         |                 | 等価発光面積            |     | cm <sup>2</sup> | 2.0 | 90 | 83  | 77  | 72   | 88 | 82  | 76 | 71 | 85   | 79 | 75 | 71 | 82 | 78   | 73  | 70 | 67 |  |     |
| 取付高さ   | 器具間隔最大限 |                 | 2.5               | 93  | 87              | 82  | 78 | 92  | 86  | 81   | 77 | 89  | 84 | 80 | 76   | 86 | 82 | 78 | 75 | 73   |     |    |    |  |     |
|        | 横方向 (A) | 縦方向 (B)         | 3.0               | 96  | 91              | 86  | 82 | 94  | 89  | 85   | 81 | 91  | 87 | 84 | 80   | 89 | 85 | 82 | 79 | 77   |     |    |    |  |     |
| 1.5m   | 1.97 m  | 1.91 m          | 4.0               | 99  | 95              | 91  | 88 | 97  | 94  | 90   | 87 | 95  | 91 | 89 | 86   | 92 | 89 | 87 | 85 | 82   |     |    |    |  |     |
| 2      | 2.63    | 2.52            | 5.0               | 101 | 97              | 94  | 92 | 99  | 96  | 93   | 91 | 97  | 94 | 92 | 89   | 94 | 92 | 90 | 88 | 85   |     |    |    |  |     |
| 2.5    | 3.28    | 3.12            | 7.0               | 103 | 100             | 98  | 96 | 102 | 99  | 97   | 95 | 99  | 97 | 95 | 93   | 97 | 95 | 93 | 92 | 89   |     |    |    |  |     |
| 3      | 3.94    | 3.73            | 10.0              | 105 | 103             | 101 | 99 | 103 | 102 | 100  | 99 | 101 | 99 | 98 | 97   | 98 | 97 | 96 | 95 | 92   |     |    |    |  |     |

