

屋内照明器具特性	
品番 (品名)	NNLK22322 + NEL2300DN
光源	LED5000_85_2900 ×1 2900.0lm
管理番号	K0191891 (0) DB1
BZ分類	BZ5/1.8/BZ4

器具効率		1 0 0 %	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		0 %	反射率	照明率 (X 0 . 0 1)																		
下方光束				1 0 0 %	Z C M																	
保守率		良 中 否	0 . 6	5 7	4 5	3 7	3 1	5 6	4 4	3 7	3 1	5 3	4 3	3 6	3 1	5 1	4 2	3 6	3 1	2 9		
			0 . 8	6 7	5 6	4 8	4 2	6 6	5 5	4 7	4 2	6 3	5 3	4 7	4 2	6 0	5 2	4 6	4 1	3 9		
			1 . 0	7 4	6 3	5 5	5 0	7 2	6 2	5 5	5 0	6 9	6 1	5 4	4 9	6 7	5 9	5 3	4 9	4 7		
			0 . 6 8	1 . 2 5	8 0	7 0	6 3	5 7	7 8	6 9	6 3	5 7	7 5	6 8	6 2	5 7	7 2	6 6	6 1	5 6	5 4	
下方投影面積		c m ²	1 . 5	8 4	7 5	6 9	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 2	7 7	7 1	6 6	6 2	5 9		
			等価発光面積		c m ²	2 . 0	9 0	8 3	7 7	7 2	8 8	8 2	7 6	7 1	8 5	7 9	7 5	7 1	8 2	7 8	7 3	7 0
取付 高さ	器具間隔最大限		2 . 5	9 3	8 7	8 2	7 8	9 2	8 6	8 1	7 7	8 9	8 4	8 0	7 6	8 6	8 2	7 8	7 5	7 3		
	横方向 (A)	縦方向 (B)	3 . 0	9 6	9 1	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 4	8 0	8 9	8 5	8 2	7 9	7 7		
1 . 5 m	1 . 9 7 m	1 . 9 1 m	4 . 0	9 9	9 5	9 1	8 8	9 7	9 4	9 0	8 7	9 5	9 1	8 9	8 6	9 2	8 9	8 7	8 5	8 2		
2	2 . 6 3	2 . 5 2	5 . 0	1 0 1	9 7	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 4	9 2	8 9	9 4	9 2	9 0	8 8	8 5		
2 . 5	3 . 2 8	3 . 1 2	7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9		
3	3 . 9 4	3 . 7 3	1 0 . 0	1 0 5	1 0 3	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2		

