

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK41109 + NEL4300CN        |
| 光源       | LED5000_85_3200 ×1 3200.0 lm |
| 管理番号     | K0192447 ( 0 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率   |           | 100 %           |           | 反射率             | 天井  | 80 %              |    |     |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|-----------|-----------------|-----------|-----------------|-----|-------------------|----|-----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|        |           |                 |           |                 | 壁   | 70                | 50 | 30  | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |           |                 |           |                 | 床   | 10 %              |    |     |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |           |                 |           |                 | 室指数 | 照明率 ( X0.01 ) ZCM |    |     |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率    |           | 良<br>中<br>否     | 0.83      | 0.6             | 55  | 43                | 35 | 30  | 54 | 42   | 35 | 30 | 51 | 41   | 34 | 29 | 49 | 40   | 33 | 29 | 27 |     |
|        |           |                 | 0.81      | 0.8             | 65  | 54                | 46 | 40  | 63 | 53   | 45 | 39 | 60 | 51   | 44 | 39 | 57 | 49   | 43 | 38 | 36 |     |
|        |           |                 | 0.77      | 1.0             | 72  | 61                | 53 | 47  | 70 | 60   | 52 | 47 | 66 | 58   | 51 | 46 | 63 | 56   | 50 | 45 | 42 |     |
|        |           |                 |           | 1.25            | 78  | 68                | 60 | 54  | 76 | 66   | 59 | 54 | 72 | 64   | 58 | 53 | 68 | 62   | 56 | 52 | 49 |     |
| 下方投影面積 |           | cm <sup>2</sup> |           | 1.5             | 82  | 72                | 65 | 60  | 80 | 71   | 64 | 59 | 76 | 69   | 63 | 58 | 72 | 66   | 61 | 57 | 54 |     |
|        |           |                 | 等価発光面積    | cm <sup>2</sup> | 2.0 | 87                | 79 | 73  | 68 | 85   | 78 | 72 | 67 | 81   | 75 | 70 | 66 | 78   | 73 | 68 | 64 | 61  |
| 取付高さ   | 器具間隔最大限   |                 |           | 2.5             | 91  | 84                | 78 | 73  | 89 | 83   | 77 | 73 | 85 | 80   | 75 | 71 | 81 | 77   | 73 | 70 | 66 |     |
|        | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0             | 93  | 87                | 82 | 78  | 91 | 86   | 81 | 77 | 87 | 83   | 79 | 75 | 84 | 80   | 77 | 73 | 70 |     |
| 1.5m   | 1.96 m    | 2.1 m           | 4.0       | 96              | 92  | 87                | 84 | 94  | 90 | 86   | 83 | 91 | 87 | 84   | 81 | 87 | 84 | 81   | 79 | 75 |    |     |
| 2      | 2.58      | 2.64            | 5.0       | 98              | 94  | 91                | 87 | 97  | 93 | 89   | 86 | 93 | 90 | 87   | 84 | 89 | 87 | 84   | 82 | 78 |    |     |
| 2.5    | 3.21      | 3.2             | 7.0       | 101             | 98  | 95                | 92 | 99  | 96 | 93   | 91 | 95 | 93 | 91   | 89 | 92 | 90 | 88   | 86 | 82 |    |     |
| 3      | 3.84      | 3.77            | 10.0      | 103             | 100 | 98                | 96 | 101 | 99 | 97   | 95 | 97 | 96 | 94   | 92 | 94 | 92 | 91   | 90 | 86 |    |     |

