

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK41109+NEL4300EX          |
| 光源       | LED5000_85_3200 ×1 3200.0 lm |
| 管理番号     | K0192447 ( 0 ) DR 1          |
| BZ分類     | BZ5                          |

| 器具効率   |         | 100 %           |         | 反射率             | 天井  | 80 %             |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|---------|-----------------|---------|-----------------|-----|------------------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|        |         |                 |         |                 | 壁   | 70               | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |         |                 |         |                 | 床   | 10 %             |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |         |                 |         |                 | 室指数 | 照明率 ( X0.01) ZCM |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率    |         | 良<br>中<br>否     | 0.83    | 0.6             | 55  | 43               | 35 | 30 | 54  | 42   | 35 | 30 | 51 | 41   | 34 | 29 | 49 | 40   | 33 | 29 | 27 |     |
|        |         |                 | 0.81    | 0.8             | 65  | 54               | 46 | 40 | 63  | 53   | 45 | 39 | 60 | 51   | 44 | 39 | 57 | 49   | 43 | 38 | 36 |     |
|        |         |                 | 0.77    | 1.0             | 72  | 61               | 53 | 47 | 70  | 60   | 52 | 47 | 66 | 58   | 51 | 46 | 63 | 56   | 50 | 45 | 42 |     |
|        |         |                 |         | 1.25            | 78  | 68               | 60 | 54 | 76  | 66   | 59 | 54 | 72 | 64   | 58 | 53 | 68 | 62   | 56 | 52 | 49 |     |
| 下方投影面積 |         | cm <sup>2</sup> |         | 1.5             | 82  | 72               | 65 | 60 | 80  | 71   | 64 | 59 | 76 | 69   | 63 | 58 | 72 | 66   | 61 | 57 | 54 |     |
|        |         |                 | 等価発光面積  | cm <sup>2</sup> | 2.0 | 87               | 79 | 73 | 68  | 85   | 78 | 72 | 67 | 81   | 75 | 70 | 66 | 78   | 73 | 68 | 64 | 61  |
| 取付高さ   | 器具間隔最大限 |                 |         | 2.5             | 91  | 84               | 78 | 73 | 89  | 83   | 77 | 73 | 85 | 80   | 75 | 71 | 81 | 77   | 73 | 70 | 66 |     |
|        | 横方向 (A) |                 | 縦方向 (B) | 3.0             | 93  | 87               | 82 | 78 | 91  | 86   | 81 | 77 | 87 | 83   | 79 | 75 | 84 | 80   | 77 | 73 | 70 |     |
| 1.5m   | 1.96 m  | 2.1 m           |         | 4.0             | 96  | 92               | 87 | 84 | 94  | 90   | 86 | 83 | 91 | 87   | 84 | 81 | 87 | 84   | 81 | 79 | 75 |     |
| 2      | 2.58    | 2.64            |         | 5.0             | 98  | 94               | 91 | 87 | 97  | 93   | 89 | 86 | 93 | 90   | 87 | 84 | 89 | 87   | 84 | 82 | 78 |     |
| 2.5    | 3.21    | 3.2             |         | 7.0             | 101 | 98               | 95 | 92 | 99  | 96   | 93 | 91 | 95 | 93   | 91 | 89 | 92 | 90   | 88 | 86 | 82 |     |
| 3      | 3.84    | 3.77            |         | 10.0            | 103 | 100              | 98 | 96 | 101 | 99   | 97 | 95 | 97 | 96   | 94 | 92 | 94 | 92   | 91 | 90 | 86 |     |

