

屋内照明器具特性	
品番 (品名)	NNLK41109 + NEL4600EX
光源	LED5000_85_6900 ×1 6900.0 lm
管理番号	K0192447 (0) DR 1
BZ分類	BZ5

器具効率			100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
						壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
						床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM																
保守率			良 中 否	0.83	0.6	55	43	35	30	54	42	35	30	51	41	34	29	49	40	33	29	27	
				0.81	0.8	65	54	46	40	63	53	45	39	60	51	44	39	57	49	43	38	36	
				0.77	1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	42	
					1.25	78	68	60	54	76	66	59	54	72	64	58	53	68	62	56	52	49	
下方投影面積			cm ²	1.5	82	72	65	60	80	71	64	59	76	69	63	58	72	66	61	57	54		
				2.0	87	79	73	68	85	78	72	67	81	75	70	66	78	73	68	64	61		
等価発光面積			cm ²	2.5	91	84	78	73	89	83	77	73	85	80	75	71	81	77	73	70	66		
				3.0	93	87	82	78	91	86	81	77	87	83	79	75	84	80	77	73	70		
1.5m			1.96 m	2.1 m	4.0	96	92	87	84	94	90	86	83	91	87	84	81	87	84	81	79	75	
2			2.58	2.64	5.0	98	94	91	87	97	93	89	86	93	90	87	84	89	87	84	82	78	
2.5			3.21	3.2	7.0	101	98	95	92	99	96	93	91	95	93	91	89	92	90	88	86	82	
3			3.84	3.77	10.0	103	100	98	96	101	99	97	95	97	96	94	92	94	92	91	90	86	

