

# 屋内照明器具特性

品番 (品名)	L G W5 1 7 6 5 B	
光源	LED5000_70_870 ×1	870.0 l m
管理番号	K0161806 ( 0 ) DB 1	
B Z 分類	B Z 5	

器具効率	75 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	8 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	67 %	室指数	照明率 ( X0.01 )																				Z C M
保守率	良 中 否 0.63 0.6 0.56	0.6	40	31	25	21	39	30	25	21	36	29	24	20	34	27	23	20	18				
		0.8	48	39	33	28	46	38	32	28	43	36	31	27	40	34	30	26	24				
		1.0	53	44	38	34	51	43	38	33	47	41	36	32	44	39	35	31	29				
		1.25	57	49	44	39	55	48	43	39	52	46	41	38	48	43	40	36	33				
下方投影面積	c m <sup>2</sup>	1.5	60	53	48	43	58	52	47	43	54	49	45	41	51	47	43	40	37				
		2.0	64	58	54	50	62	57	53	49	59	54	50	47	55	51	48	46	42				
取付高さ	器具間隔最大限		2.5	67	62	58	54	65	60	56	53	61	57	54	51	58	55	52	49	46			
	横方向 ( A )	縦方向 ( B )	3.0	69	64	61	57	67	63	59	56	63	60	57	54	60	57	54	52	48			
H m	1.32 H m	1.31 H m	4.0	71	68	65	62	69	66	63	61	66	63	60	58	62	60	58	56	52			
			5.0	73	70	67	65	71	68	66	63	67	65	63	61	64	62	60	58	54			
			7.0	75	72	70	68	73	71	69	67	69	67	66	64	65	64	63	62	57			
			10.0	76	74	73	71	74	72	71	70	70	69	68	67	67	66	65	64	60			

