

屋内照明器具特性

品番 (品名)	L G W 5 1 7 7 5 W															
光源	LED5000_70_530 x1 530.0 l m															
管理番号	K0161775 (0) DB 1															
B Z 分類	B Z 5															

器具効率	78 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	9 %																			
下方光束	69 %																			
室指数	照明率 (X 0 . 0 1) Z C M																			
保守率	良 中 否	0.63	0.6	4.2	3.2	2.6	2.2	4.0	3.1	2.6	2.2	3.8	3.0	2.5	2.1	3.5	2.8	2.4	2.0	1.8
		0.6	0.8	4.9	4.0	3.4	2.9	4.8	3.9	3.3	2.9	4.4	3.7	3.2	2.8	4.2	3.5	3.1	2.7	2.5
		0.56	1.0	5.4	4.6	4.0	3.5	5.2	4.5	3.9	3.5	4.9	4.2	3.7	3.4	4.6	4.0	3.6	3.3	3.0
			1.25	5.9	5.1	4.5	4.1	5.7	5.0	4.4	4.0	5.3	4.7	4.3	3.9	5.0	4.5	4.1	3.8	3.5
下方投影面積	c m ²	1.5	6.2	5.5	4.9	4.5	6.0	5.4	4.8	4.4	5.6	5.1	4.6	4.3	5.3	4.8	4.5	4.1	3.8	
		2.0	6.6	6.0	5.6	5.1	6.4	5.9	5.4	5.1	6.1	5.6	5.2	4.9	5.7	5.3	5.0	4.7	4.4	
取付高さ	器具間隔最大限		2.5	6.9	6.4	6.0	5.6	6.7	6.2	5.8	5.5	6.3	5.9	5.6	5.3	6.0	5.7	5.4	5.1	4.8
	横方向 (A)	縦方向 (B)	3.0	7.1	6.7	6.3	5.9	6.9	6.5	6.1	5.8	6.5	6.2	5.9	5.6	6.2	5.9	5.6	5.4	5.0
H m	1.31 H m	1.31 H m	4.0	7.4	7.0	6.7	6.4	7.2	6.8	6.5	6.3	6.8	6.5	6.3	6.0	6.4	6.2	6.0	5.8	5.4
			5.0	7.5	7.2	6.9	6.7	7.3	7.0	6.8	6.6	6.9	6.7	6.5	6.3	6.6	6.4	6.2	6.1	5.6
			7.0	7.7	7.5	7.3	7.1	7.5	7.3	7.1	6.9	7.1	7.0	6.8	6.6	6.8	6.6	6.5	6.4	5.9
			10.0	7.8	7.7	7.5	7.4	7.7	7.5	7.3	7.2	7.3	7.2	7.0	6.9	6.9	6.8	6.7	6.6	6.2

