

屋内照明器具特性

品番 (品名)	NTN81341 + NTN81993	
光源	LED4000_70_1770 x1 1770.0 lm	
管理番号	K0163042 (0) DR1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	12 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	88 %		室指数	照明率 (X0.01)																			
保守率	良	0.69	0.6	53	41	33	28	51	40	32	27	48	38	31	26	45	36	30	26	23			
	中	0.67	0.8	63	51	43	37	61	50	42	36	56	47	40	35	53	45	39	34	31			
	否	0.63	1.0	69	58	50	44	67	56	49	43	62	53	47	42	58	51	45	40	37			
			1.25	75	65	57	51	72	63	56	50	68	60	53	48	63	56	51	47	43			
下方投影面積	c m ²		1.5	79	70	62	56	76	68	61	55	71	64	58	53	67	61	56	51	47			
等価発光面積	c m ²		2.0	85	77	70	64	82	75	68	63	77	71	65	61	72	67	62	59	54			
取付高さ	器具間隔最大限		2.5	88	81	75	70	86	79	74	69	80	75	70	66	75	71	67	64	59			
	横方向 (A)	縦方向 (B)		3.0	91	85	79	74	88	82	77	73	83	78	74	70	78	74	70	67	62		
1.5m	2 m	2.08 m	4.0	94	89	84	80	91	87	83	79	86	82	79	76	81	78	75	72	67			
2	2.64	2.64	5.0	96	92	88	84	93	89	86	83	88	85	82	79	83	81	78	76	70			
2.5	3.28	3.21	7.0	99	95	92	89	96	93	90	87	91	88	86	84	86	84	82	80	74			
3	3.92	3.81	10.0	100	98	96	93	98	96	93	91	93	91	89	87	88	86	85	84	78			

