

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK42525J + NEL4300EX       |
| 光源       | LED5000_85_3120 ×1 3120.0 lm |
| 管理番号     | K0192149 ( 0 ) D 1           |
| BZ分類     | BZ5                          |

| 器具効率         |                 | 100 %           | 反射率  | 天井                | 80 % |     |    |     | 70 % |    |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------------|-----------------|-----------------|------|-------------------|------|-----|----|-----|------|----|----|-----|------|----|----|----|------|----|----|----|-----|
|              |                 |                 |      | 壁                 | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|              |                 |                 |      | 床                 | 10 % |     |    |     | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
| 上方光束<br>下方光束 |                 | 100 %           | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |    |     |      |    |    |     |      |    |    |    |      |    |    |    |     |
| 保守率          |                 | 良<br>中<br>否     | 0.83 | 0.6               | 56   | 44  | 36 | 30  | 55   | 43 | 36 | 30  | 52   | 42 | 35 | 30 | 50   | 41 | 35 | 30 | 28  |
|              |                 |                 | 0.81 | 0.8               | 66   | 54  | 46 | 41  | 65   | 54 | 46 | 41  | 62   | 52 | 45 | 40 | 59   | 51 | 45 | 40 | 38  |
|              |                 |                 | 0.77 | 1.0               | 73   | 62  | 54 | 48  | 71   | 61 | 53 | 48  | 68   | 59 | 53 | 47 | 65   | 58 | 52 | 47 | 45  |
|              |                 |                 |      | 1.25              | 79   | 69  | 61 | 55  | 77   | 68 | 61 | 55  | 74   | 66 | 60 | 55 | 71   | 64 | 59 | 54 | 52  |
| 下方投影面積       |                 | cm <sup>2</sup> | 1.5  | 83                | 74   | 67  | 61 | 81  | 73   | 66 | 61 | 78  | 71   | 65 | 60 | 75 | 69   | 64 | 60 | 57 |     |
| 等価発光面積       |                 |                 | 2.0  | 89                | 81   | 75  | 70 | 87  | 80   | 74 | 69 | 84  | 78   | 73 | 68 | 81 | 76   | 71 | 67 | 65 |     |
| 取付高さ         | 器具間隔最大限         |                 | 2.5  | 92                | 86   | 80  | 75 | 91  | 84   | 79 | 75 | 87  | 82   | 78 | 74 | 84 | 80   | 76 | 73 | 70 |     |
|              | 横方向 (A) 縦方向 (B) |                 | 3.0  | 95                | 89   | 84  | 80 | 93  | 88   | 83 | 79 | 90  | 85   | 82 | 78 | 87 | 83   | 80 | 77 | 74 |     |
| 1.5m         | 1.97 m          | 2.11 m          | 4.0  | 98                | 93   | 89  | 86 | 96  | 92   | 88 | 85 | 93  | 90   | 87 | 84 | 91 | 88   | 85 | 82 | 80 |     |
| 2            | 2.59            | 2.65            | 5.0  | 100               | 96   | 93  | 90 | 98  | 95   | 92 | 89 | 96  | 93   | 90 | 87 | 93 | 90   | 88 | 86 | 83 |     |
| 2.5          | 3.23            | 3.21            | 7.0  | 102               | 99   | 97  | 94 | 101 | 98   | 96 | 93 | 98  | 96   | 94 | 92 | 95 | 94   | 92 | 90 | 87 |     |
| 3            | 3.85            | 3.79            | 10.0 | 104               | 102  | 100 | 98 | 103 | 101  | 99 | 97 | 100 | 98   | 97 | 95 | 97 | 96   | 95 | 94 | 91 |     |

