

# 屋内照明器具特性

品番 (品名)	L G W 8 0 3 5 1									
光源	LED2700_70_197.8 ×1					197.8 1 m				
管理番号	K0141568 ( 0 ) DR 1									
B Z 分類	B Z 6									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	52 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	48 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 ( X 0.01 )																Z C M	
保守率	良 中 否 0.63 0.6 0.56	0.6	48	36	29	24	44	34	27	22	37	29	23	19	30	24	20	16	11	
		0.8	57	45	38	32	52	42	35	30	43	36	30	26	35	30	26	22	16	
		1.0	63	52	44	39	58	48	41	36	48	41	36	31	39	34	30	27	19	
		1.25	68	58	51	45	63	54	48	42	52	46	41	37	43	38	34	31	22	
下方投影面積	c m <sup>2</sup>	1.5	72	63	56	51	66	58	52	47	55	50	45	41	46	41	38	35	24	
		2.0	77	70	64	58	71	65	59	55	60	55	51	47	49	46	42	40	28	
取付高さ	器具間隔最大限		2.5	81	74	69	64	75	69	64	60	63	58	55	51	52	49	46	43	31
	横方向 ( A )	縦方向 ( B )	3.0	83	77	72	68	77	72	67	63	65	61	58	55	54	51	48	46	33
H m	1.39 H m	1.31 H m	4.0	86	82	77	74	80	76	72	69	68	64	62	59	56	54	52	50	36
			5.0	88	84	81	77	82	78	75	72	69	67	64	62	58	56	54	52	37
			7.0	91	87	85	82	84	81	79	76	71	69	67	66	59	58	57	55	40
			10.0	92	90	88	86	86	84	82	80	73	72	70	69	61	60	59	58	42

