

屋内照明器具特性

品番 (品名)	LSEB1168														
光源	LED6200_70_4299 x1 4299.0 lm														
管理番号	K0171160(0)DR1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	8%	室指数	照明率 (X0.01)																ZCM		
下方光束	92%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	55	43	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25		
		0.8	65	53	45	39	63	52	44	39	59	50	43	38	55	48	42	37	34		
		1.0	71	60	52	46	69	59	51	46	65	56	50	45	61	54	48	44	41		
		1.25	77	67	59	54	75	65	58	53	70	63	57	52	66	60	55	50	47		
下方投影面積	c m ²	1.5	81	72	65	59	79	70	64	58	74	67	61	57	70	64	59	55	52		
		2.0	87	79	72	67	84	77	71	66	80	74	69	64	76	71	66	63	59		
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	76	72	83	78	74	70	79	75	71	68	63	
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	90	85	80	76	86	81	77	74	82	78	74	71	67	
H m	1.26 H m	1.26 H m	4.0	96	91	87	83	93	89	85	82	89	85	82	79	85	82	79	77	72	
			5.0	98	94	90	87	95	92	88	85	91	88	85	83	87	84	82	80	75	
			7.0	100	97	94	92	98	95	92	90	93	91	89	87	89	87	86	84	79	
			10.0	102	100	97	95	100	98	96	94	95	94	92	90	91	90	89	87	82	

