

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | NNLK42762J + FSK41259 + NEL4 |
| 光源       | LED5000_85_4310 ×1 4310.0 lm |
| 管理番号     | K0192930 ( 0 ) DB 1          |
| BZ分類     | BZ2                          |

| 器具効率             |           | 100 %                              | 反射率  | 天井                | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |    |    |    | 0 % |
|------------------|-----------|------------------------------------|------|-------------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|----|----|----|-----|
|                  |           |                                    |      | 壁                 | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50 | 30 | 10 | 0 % |
|                  |           |                                    |      | 床                 | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |    |    |    | 0 % |
| 上方光束<br>下方光束     |           | 100 %                              | 室指数  | 照明率 ( X0.01 ) ZCM |      |     |     |     |      |     |     |     |      |     |     |     |      |    |    |    |     |
| 保守率              |           | 良<br>中<br>否                        | 0.81 | 0.6               | 69   | 59  | 53  | 49  | 67   | 58  | 53  | 49  | 66   | 58  | 52  | 48  | 64   | 57 | 52 | 48 | 47  |
|                  |           |                                    | 0.77 | 0.8               | 78   | 70  | 64  | 60  | 77   | 69  | 64  | 60  | 75   | 68  | 63  | 59  | 73   | 67 | 62 | 59 | 57  |
|                  |           |                                    | 0.68 | 1.0               | 84   | 77  | 71  | 67  | 83   | 76  | 71  | 67  | 81   | 75  | 70  | 67  | 79   | 73 | 69 | 66 | 64  |
|                  |           |                                    |      | 1.25              | 89   | 82  | 77  | 74  | 88   | 82  | 77  | 73  | 86   | 80  | 76  | 73  | 83   | 79 | 75 | 72 | 71  |
| 下方投影面積<br>等価発光面積 |           | cm <sup>2</sup><br>cm <sup>2</sup> |      | 1.5               | 92   | 86  | 82  | 78  | 91   | 86  | 81  | 78  | 89   | 84  | 80  | 77  | 86   | 83 | 79 | 77 | 75  |
|                  |           |                                    |      | 2.0               | 96   | 92  | 88  | 84  | 95   | 91  | 87  | 84  | 93   | 89  | 86  | 83  | 90   | 87 | 85 | 82 | 80  |
| 取付<br>高さ         | 器具間隔最大限   |                                    |      | 2.5               | 99   | 95  | 91  | 88  | 98   | 94  | 91  | 88  | 95   | 92  | 89  | 87  | 93   | 90 | 88 | 86 | 84  |
|                  | 横方向 ( A ) | 縦方向 ( B )                          |      | 3.0               | 100  | 97  | 94  | 91  | 99   | 96  | 93  | 91  | 97   | 94  | 92  | 90  | 95   | 92 | 90 | 89 | 86  |
| 1.5m             | 1.8 m     | 1.89 m                             |      | 4.0               | 103  | 100 | 97  | 95  | 101  | 99  | 97  | 95  | 99   | 97  | 95  | 93  | 97   | 95 | 93 | 92 | 89  |
| 2                | 2.38      | 2.34                               |      | 5.0               | 104  | 101 | 99  | 98  | 102  | 100 | 99  | 97  | 100  | 98  | 97  | 95  | 98   | 96 | 95 | 94 | 91  |
| 2.5              | 2.97      | 2.81                               |      | 7.0               | 105  | 103 | 102 | 101 | 104  | 102 | 101 | 100 | 102  | 100 | 99  | 98  | 99   | 98 | 97 | 96 | 94  |
| 3                | 3.55      | 3.3                                |      | 10.0              | 106  | 105 | 104 | 103 | 105  | 104 | 103 | 102 | 103  | 102 | 101 | 100 | 100  | 99 | 98 | 95 | 95  |

