

屋内照明器具特性	
品番 (品名)	NDNN7 1 5 0 0
光源	NNU141155LZ9 ×1      1580.0 l m
管理番号	K0133642 ( 1 ) DR 1
B Z 分類	BZ1 / 1.4 / BZ2 / 8.5 / BZ1

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	93 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.81	0.6	67	59	53	50	66	58	53	50	64	57	53	50	63	57	53	49	48
	中	0.77	0.8	75	67	62	59	74	67	62	59	72	66	62	58	70	65	61	58	57
	否	0.68	1.0	80	73	68	65	79	73	68	65	77	71	67	64	75	70	67	64	62
			1.25	84	78	74	70	83	78	73	70	81	76	73	70	79	75	72	69	68
下方投影面積			1.5	87	82	77	74	86	81	77	74	84	79	76	73	82	78	75	73	71
			2.0	90	86	83	80	89	85	82	79	87	84	81	79	85	82	80	78	76
取付高さ	器具間隔最大限		2.5	93	89	86	83	91	88	85	83	89	86	84	82	87	85	83	81	79
	横方向 (A)	縦方向 (B)	3.0	94	91	88	86	93	90	87	85	91	88	86	84	89	87	85	83	81
H m	0.76 H m	0.76 H m	4.0	96	93	91	89	95	92	90	89	92	91	89	87	90	89	87	86	84
			5.0	97	95	93	91	96	94	92	91	94	92	91	89	92	90	89	88	86
			7.0	98	97	95	94	97	96	94	93	95	94	93	92	93	92	91	90	88
			10.0	99	98	97	96	98	97	96	95	96	95	94	93	94	93	92	92	89

