

屋内照明器具特性

| | | |
|---------|--------------------|-----------|
| 品番 (品名) | NDG10800S (JYOUJI) | |
| 光源 | NNU140105KLE9 x1 | 1130.0 lm |
| 管理番号 | K0160026 (0) DR1 | |
| BZ分類 | BZ2 / 8.5 / BZ1 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-------------------------------------|----------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|
| 器具効率 | 84 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| 上方光束 | 0 % | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 下方光束 | 84 % | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 0.83 0.81 0.77 | 0.6 | 57 | 49 | 44 | 40 | 56 | 49 | 44 | 40 | 55 | 48 | 44 | 40 | 53 | 47 | 43 | 40 | 39 | |
| | | 0.8 | 66 | 59 | 54 | 51 | 65 | 58 | 54 | 51 | 63 | 58 | 53 | 50 | 62 | 57 | 53 | 50 | 49 | |
| | | 1.0 | 71 | 65 | 61 | 57 | 70 | 64 | 60 | 57 | 68 | 63 | 60 | 57 | 67 | 62 | 59 | 57 | 55 | |
| | | 1.25 | 75 | 70 | 66 | 63 | 74 | 69 | 66 | 63 | 72 | 68 | 65 | 62 | 71 | 67 | 64 | 62 | 60 | |
| 下方投影面積 | c m ² | 1.5 | 78 | 73 | 69 | 67 | 77 | 72 | 69 | 66 | 75 | 71 | 68 | 66 | 73 | 70 | 67 | 65 | 64 | |
| | | 2.0 | 81 | 77 | 74 | 72 | 80 | 77 | 74 | 71 | 78 | 75 | 73 | 71 | 76 | 74 | 72 | 70 | 68 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 83 | 80 | 77 | 75 | 82 | 79 | 77 | 75 | 80 | 78 | 76 | 74 | 78 | 76 | 75 | 73 | 71 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 84 | 82 | 79 | 77 | 83 | 81 | 79 | 77 | 81 | 79 | 78 | 76 | 80 | 78 | 76 | 75 | 73 |
| H m | 1.00 H m | 1.05 H m | 4.0 | 86 | 84 | 82 | 80 | 85 | 83 | 81 | 80 | 83 | 82 | 80 | 79 | 81 | 80 | 79 | 78 | 76 |
| | | | 5.0 | 87 | 85 | 84 | 82 | 86 | 84 | 83 | 82 | 84 | 83 | 82 | 80 | 82 | 81 | 80 | 79 | 77 |
| | | | 7.0 | 88 | 87 | 86 | 85 | 87 | 86 | 85 | 84 | 85 | 84 | 83 | 82 | 83 | 83 | 82 | 81 | 79 |
| | | | 10.0 | 89 | 88 | 87 | 86 | 88 | 87 | 86 | 86 | 86 | 85 | 85 | 84 | 84 | 84 | 83 | 83 | 80 |

