

屋内照明器具特性

品番 (品名)	NDNN7 1 5 0 4									
光源	NNU241105LZ9 ×1					2010.0 1 m				
管理番号	K0133661 (0) DR 1									
B Z 分類	B Z 1									

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																Z C M		
下方光束	88 %																				
保守率	良 中 否	0.81	0.6	67	60	56	53	66	60	56	53	65	59	55	52	63	58	55	52	51	
		0.77	0.8	74	67	63	60	73	67	63	60	71	66	63	60	70	65	62	60	58	
		0.68	1.0	78	72	68	65	77	72	68	65	75	71	67	65	73	70	67	64	63	
			1.25	81	76	73	70	80	76	72	69	78	74	71	69	77	73	71	69	67	
下方投影面積	c m ²	1.5	83	79	76	73	82	78	75	72	80	77	74	72	79	76	73	71	70		
		2.0	86	83	80	77	85	82	79	77	83	80	78	76	81	79	77	75	74		
取付高さ	器具間隔最大限		2.5	88	85	82	80	87	84	82	80	85	83	81	79	83	81	79	78	76	
	横方向 (A)	縦方向 (B)	3.0	89	87	84	82	88	86	84	82	86	84	82	81	84	83	81	80	78	
H m	0.76 H m	0.76 H m	4.0	91	89	87	85	90	88	86	85	88	86	85	83	86	84	83	82	80	
			5.0	92	90	88	87	91	89	88	86	89	87	86	85	87	86	85	84	82	
			7.0	93	91	90	89	92	90	89	88	90	89	88	87	88	87	86	85	83	
			10.0	93	92	92	91	92	91	91	90	90	90	89	88	88	88	87	87	84	

