

屋内照明器具特性

品番 (品名)	NDNN7 1 5 0 4				
光源	NNU240105LZ9 ×1 2050.0 l m				
管理番号	K0133663 (0) DR 1				
BZ分類	BZ1 / 3.5 / BZ2 / 8.5 / BZ1				

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	86 %		床	10 %				10 %				10 %				10 %				0 %
室指数			照明率 (X0.01)																ZCM	
保守率	良 中 否	0.81	0.6	63	56	51	48	62	56	51	48	61	55	51	48	60	54	51	48	47
		0.77	0.8	70	64	59	56	69	63	59	56	68	62	59	56	66	61	58	56	54
			1.0	74	69	64	61	73	68	64	61	72	67	64	61	70	66	63	61	59
		0.68	1.25	78	73	69	66	77	72	69	66	75	71	68	65	73	70	67	65	63
下方投影面積	c m ²	1.5	80	76	72	69	79	75	72	69	77	74	71	68	76	73	70	68	66	
		2.0	83	80	77	74	82	79	76	74	80	77	75	73	79	76	74	72	71	
取付高さ	器具間隔最大限		2.5	85	82	79	77	84	81	79	77	82	80	78	76	80	78	77	75	73
	横方向 (A)	縦方向 (B)	3.0	87	84	81	79	86	83	81	79	84	81	80	78	82	80	78	77	75
H m	1.00 H m	1.00 H m	4.0	88	86	84	82	87	85	83	82	85	83	82	81	83	82	81	79	77
			5.0	89	87	86	84	88	86	85	84	86	85	83	82	84	83	82	81	79
			7.0	90	89	88	86	89	88	87	86	87	86	85	84	85	84	84	83	81
			10.0	91	90	89	88	90	89	88	87	88	87	87	86	86	86	85	84	82

