

# 屋内照明器具特性

品番 (品名)	NDNN7 1 5 0 0	
光源	NNU140155LZ9 ×1	1610.0 l m
管理番号	K0133646 (4) DR 1	
BZ分類	BZ2	

器具効率	90 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	90 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.81	0.6	62	54	48	44	61	53	48	44	60	52	48	44	58	52	47	44	43
	中	0.77	0.8	71	63	58	54	70	63	58	54	68	61	57	54	66	61	57	53	52
	否	0.68	1.0	76	69	64	60	75	68	64	60	73	67	63	60	71	66	63	60	58
			1.25	80	74	70	66	79	74	69	66	77	72	68	65	75	71	68	65	63
下方投影面積	c m <sup>2</sup>		1.5	83	78	73	70	82	77	73	70	80	76	72	69	78	74	71	69	67
等価発光面積	c m <sup>2</sup>		2.0	87	82	79	76	86	82	78	75	83	80	77	75	81	79	76	74	72
取付高さ	器具間隔最大限		2.5	89	85	82	79	88	84	82	79	86	83	80	78	84	81	79	77	75
	横方向 (A)	縦方向 (B)	3.0	91	87	85	82	89	86	84	82	87	85	83	81	85	83	81	80	78
H m	1.14 H m	1.14 H m	4.0	92	90	88	86	91	89	87	85	89	87	85	84	87	86	84	83	81
			5.0	94	92	90	88	92	91	89	87	90	89	87	86	88	87	86	85	82
			7.0	95	93	92	91	94	92	91	90	92	90	89	88	90	89	88	87	85
			10.0	96	95	94	93	95	94	93	92	93	92	91	90	91	90	89	89	86

