

屋内照明器具特性

品番(品名)	NDNN71501									
光源	NNU141105LZ9 ×1					1110.0 l m				
管理番号	K0132246(2)DR1									
BZ分類	BZ2/0.7/BZ1/0.9/BZ2									

器具効率	96%	天井	80%				70%				50%				30%				0%		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	反射率	床	10%				10%				10%				10%				0%	
下方光束	96%		室指数	照明率 (×0.01) ZCM																	
保守率	良	0.81	0.6	68	60	54	51	67	59	54	51	66	59	54	50	64	58	53	50	49	
	中	0.77	0.8	77	69	64	60	76	69	64	60	74	68	63	60	72	67	63	59	58	
	否	0.68	1.0	82	75	70	66	81	74	70	66	79	73	69	66	77	72	68	66	64	
			1.25	86	80	76	72	85	80	75	72	83	78	74	71	81	77	74	71	69	
下方投影面積		c m ²	1.5	89	84	80	76	88	83	79	76	86	82	78	75	84	80	77	75	73	
等価発光面積		c m ²	2.0	93	88	85	82	92	88	84	81	89	86	83	81	87	84	82	80	78	
取付高さ	器具間隔最大限		2.5	95	91	88	85	94	90	87	85	92	89	86	84	89	87	85	83	81	
	横方向(A)	縦方向(B)	3.0	97	93	91	88	95	92	90	88	93	91	88	86	91	89	87	85	83	
H m	0.76 H m	0.76 H m	4.0	98	96	94	92	97	95	93	91	95	93	91	90	93	91	90	88	86	
			5.0	100	97	96	94	98	96	95	93	96	95	93	92	94	93	91	90	88	
			7.0	101	99	98	97	100	98	97	96	97	96	95	94	95	94	93	93	90	
			10.0	102	101	100	99	101	100	99	98	98	98	97	96	96	96	95	94	92	

