

# 屋内照明器具特性

品番 (品名)	L G W 8 0 2 2 3 K									
光源	LED2700_70_195 ×1					195.0 l m				
管理番号	K0158606 ( 0 ) DB 1									
B Z 分類	B Z 5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	50 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	50 %		室指数	照明率 ( X 0.01 )																Z C M
保守率	良 中 否 0.63 0.6 0.56	0.6	4.9	3.7	3.0	2.5	4.5	3.5	2.8	2.4	3.8	3.0	2.5	2.1	3.1	2.5	2.1	1.8	1.3	
		0.8	5.8	4.7	3.9	3.4	5.3	4.3	3.7	3.2	4.5	3.7	3.2	2.8	3.7	3.1	2.7	2.4	1.8	
		1.0	6.4	5.3	4.6	4.0	5.9	5.0	4.3	3.8	5.0	4.3	3.7	3.3	4.1	3.6	3.2	2.9	2.1	
		1.25	6.9	6.0	5.3	4.7	6.4	5.6	4.9	4.4	5.4	4.8	4.3	3.9	4.5	4.0	3.6	3.3	2.4	
下方投影面積	c m <sup>2</sup>	1.5	7.3	6.5	5.8	5.2	6.8	6.0	5.4	4.9	5.7	5.1	4.7	4.3	4.8	4.3	4.0	3.7	2.7	
		2.0	7.9	7.1	6.5	6.0	7.3	6.6	6.1	5.7	6.2	5.7	5.3	4.9	5.1	4.8	4.5	4.2	3.1	
取付高さ	器具間隔最大限		2.5	8.2	7.6	7.0	6.6	7.6	7.0	6.6	6.2	6.4	6.0	5.7	5.4	5.4	5.1	4.8	3.4	
	横方向 ( A )	縦方向 ( B )	3.0	8.4	7.9	7.4	7.0	7.8	7.3	6.9	6.5	6.6	6.3	6.0	5.7	5.6	5.3	5.0	3.6	
1.5 m	1.97 m	1.96 m	4.0	8.7	8.3	7.9	7.5	8.1	7.7	7.4	7.1	6.9	6.6	6.4	6.1	5.8	5.6	5.4	3.8	
2	2.63	2.59	5.0	8.9	8.5	8.2	7.9	8.3	8.0	7.7	7.4	7.1	6.8	6.6	6.4	5.9	5.8	5.6	4.0	
2.5	3.29	3.24	7.0	9.1	8.9	8.6	8.3	8.5	8.3	8.0	7.8	7.3	7.1	6.9	6.8	6.1	6.0	5.9	4.2	
3	3.95	3.89	10.0	9.3	9.1	8.9	8.7	8.7	8.5	8.3	8.1	7.4	7.3	7.2	7.0	6.3	6.2	6.1	4.4	

