

屋内照明器具特性

| | | | | | | | | | | | | | | | | |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | NNCF20115 (JYOUJI) | | | | | | | | | | | | | | | |
| 光源 | LED5000_85_1800 x1 1800.0 lm | | | | | | | | | | | | | | | |
| 管理番号 | K0171711 (0) DR 1 | | | | | | | | | | | | | | | |
| BZ分類 | BZ7/0.7/BZ6 | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|---------|---------|--------------|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | | | 反射率 | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | | | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 上方光束 | 50% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | | |
| 下方光束 | 50% | | | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 | 0.83 | 0.6 | 47 | 35 | 27 | 22 | 43 | 32 | 26 | 21 | 36 | 28 | 22 | 18 | 29 | 23 | 18 | 15 | 10 | |
| | 中 | 0.81 | 0.8 | 56 | 44 | 36 | 30 | 51 | 41 | 34 | 28 | 43 | 35 | 29 | 25 | 35 | 29 | 24 | 21 | 14 | |
| | 否 | 0.77 | 1.0 | 62 | 51 | 43 | 37 | 57 | 47 | 40 | 34 | 47 | 40 | 34 | 30 | 39 | 33 | 29 | 25 | 17 | |
| | | | 1.25 | 67 | 57 | 49 | 43 | 62 | 53 | 46 | 41 | 52 | 45 | 39 | 35 | 42 | 37 | 33 | 30 | 21 | |
| 下方投影面積 | | | 1.5 | 71 | 62 | 54 | 49 | 65 | 57 | 51 | 45 | 55 | 48 | 43 | 39 | 45 | 40 | 36 | 33 | 23 | |
| | | | 2.0 | 77 | 69 | 62 | 56 | 71 | 64 | 58 | 53 | 59 | 54 | 49 | 45 | 49 | 45 | 41 | 38 | 27 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 80 | 73 | 67 | 62 | 74 | 68 | 62 | 58 | 62 | 58 | 53 | 50 | 52 | 48 | 45 | 42 | 30 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 83 | 76 | 71 | 66 | 76 | 71 | 66 | 62 | 65 | 60 | 57 | 53 | 53 | 50 | 47 | 45 | 32 | |
| 1.5m | 2.31m | 2m | 4.0 | 86 | 81 | 76 | 72 | 79 | 75 | 71 | 67 | 67 | 64 | 61 | 58 | 56 | 53 | 51 | 49 | 35 | |
| 2 | 3.06 | 2.58 | 5.0 | 88 | 84 | 80 | 76 | 81 | 78 | 74 | 71 | 69 | 66 | 64 | 61 | 58 | 56 | 53 | 52 | 37 | |
| 2.5 | 3.81 | 3.18 | 7.0 | 90 | 87 | 84 | 81 | 84 | 81 | 78 | 76 | 71 | 69 | 67 | 65 | 60 | 58 | 56 | 55 | 40 | |
| 3 | 4.57 | 3.79 | 10.0 | 92 | 90 | 87 | 85 | 86 | 84 | 81 | 79 | 73 | 72 | 70 | 68 | 61 | 60 | 59 | 58 | 42 | |

