

屋内照明器具特性

品番 (品名)	NNCF20615 (J YOUJI)															
光源	LED5000_85_1800 ×1 1800.0 lm															
管理番号	K0171711 (0) DR 1															
BZ分類	BZ7 / 0.7 / BZ6															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	50 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %		室指数																	
保守率	良 0.83 中 0.81 否 0.77	照明率 (X0.01)																Z CM		
		0.6	47	35	27	22	43	32	26	21	36	28	22	18	29	23	18		15	10
下方投影面積	c m ²	1.25	67	57	49	43	62	53	46	41	52	45	39	35	42	37	33	30	21	
		1.5	71	62	54	49	65	57	51	45	55	48	43	39	45	40	36	33	23	
等価発光面積	c m ²	2.0	77	69	62	56	71	64	58	53	59	54	49	45	49	45	41	38	27	
		2.5	80	73	67	62	74	68	62	58	62	58	53	50	52	48	45	42	30	
取付高さ	器具間隔最大限		3.0	83	76	71	66	76	71	66	62	65	60	57	53	53	50	47	45	32
	横方向 (A)	縦方向 (B)																		
1.5m	2.31 m	2 m	4.0	86	81	76	72	79	75	71	67	67	64	61	58	56	53	51	49	35
2	3.06	2.58	5.0	88	84	80	76	81	78	74	71	69	66	64	61	58	56	53	52	37
2.5	3.81	3.18	7.0	90	87	84	81	84	81	78	76	71	69	67	65	60	58	56	55	40
3	4.57	3.79	10.0	92	90	87	85	86	84	81	79	73	72	70	68	61	60	59	58	42

