

屋内照明器具特性

品番 (品名)	NNF 4 1 7 7 2 J									
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1 m									
管理番号	K0129155(1)DB1									
BZ分類	BZ4									

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	88 %		床	10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																ZCM			
保守率	良 中 否	0.81	0.6	53	43	37	32	52	43	37	32	50	42	36	32	48	41	36	32	31
		0.77	0.8	62	53	47	42	61	52	46	42	59	51	46	42	57	50	45	42	40
			1.0	68	59	53	49	67	59	53	49	64	57	52	48	62	56	52	48	46
		0.68	1.25	73	65	60	55	72	65	59	55	69	63	58	55	67	62	58	54	52
下方投影面積	c m ²	1.5	76	69	64	60	75	69	64	60	72	67	63	59	70	66	62	59	57	
		2.0	81	75	71	67	79	74	70	66	77	73	69	66	75	71	68	65	63	
取付高さ	器具間隔最大限		2.5	83	79	75	71	82	78	74	71	80	76	73	70	77	74	72	69	67
	横方向 (A)	縦方向 (B)	3.0	85	81	78	75	84	80	77	74	82	78	76	73	79	77	74	72	70
1.5m	2.05 m	2.18 m	4.0	88	84	82	79	86	84	81	78	84	82	79	77	82	80	78	76	74
2	2.73	2.76	5.0	89	86	84	82	88	86	83	81	86	84	82	80	84	82	80	79	76
2.5	3.41	3.35	7.0	91	89	87	85	90	88	86	85	87	86	84	83	85	84	83	82	79
3	4.08	3.95	10.0	92	91	89	88	91	90	88	87	89	88	87	86	87	86	85	84	82

