

屋内照明器具特性	
品番 (品名)	NDW10800S
光源	NNU141105KLE9 x1 1130.0 lm
管理番号	K0160021(0)DR1
BZ分類	BZ2/8.5/BZ1

器具効率	84%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	84%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 0.83	0.6	58	50	45	41	57	49	44	41	55	49	44	41	54	48	44	41	39	
	中 0.81	0.8	66	59	54	51	65	58	54	51	63	58	53	50	62	57	53	50	49	
	否 0.77	1.0	71	65	60	57	70	64	60	57	68	63	59	56	66	62	59	56	55	
			1.25	75	70	66	62	74	69	65	62	72	68	64	62	70	67	64	61	60
下方投影面積	cm <sup>2</sup>	1.5	78	73	69	66	77	72	69	66	75	71	68	65	73	70	67	65	63	
		2.0	81	77	74	71	80	77	74	71	78	75	73	70	76	74	72	70	68	
取付高さ	器具間隔最大限		2.5	83	80	77	75	82	79	77	74	80	78	76	74	78	76	74	73	71
	横方向 (A)	縦方向 (B)	3.0	85	82	79	77	84	81	79	77	82	79	78	76	80	78	76	75	73
Hm	0.64Hm	0.64Hm	4.0	86	84	82	80	85	83	81	80	83	82	80	79	81	80	79	78	76
			5.0	87	85	84	82	86	85	83	82	84	83	82	80	82	81	80	79	77
			7.0	88	87	86	85	87	86	85	84	85	84	83	83	84	83	82	81	79
			10.0	89	88	87	86	88	87	86	86	86	85	85	84	84	84	83	83	80

