

# 屋内照明器具特性

品番 (品名)	L G W8 1 5 1 2									
光源	LED2700_70_294 ×1					294.0 l m				
管理番号	K0142279 ( 0 ) DB 1									
B Z 分類	B Z 3									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	50 %	室指数																		照明率 ( X0.01 )																		Z C M																	
下方光束	50 %																																																						
保守率	良 中 否	0.63	0.6	0.56	0.6	54	43	37	32	50	41	35	31	43	36	31	28	37	31	28	25	20																																	
		0.6	0.6	0.6	0.6	63	53	46	41	58	50	44	39	50	44	39	36	43	38	34	32	25																																	
		0.6	0.6	0.6	0.6	69	60	53	48	64	56	50	46	55	49	45	41	47	42	39	37	29																																	
		0.56	0.56	0.56	0.56	74	66	60	55	69	62	56	52	59	54	50	46	50	46	43	41	32																																	
下方投影面積	c m <sup>2</sup>	1.25	1.5	2.0	2.5	74	66	60	55	69	62	56	52	59	54	50	46	50	46	43	41	32																																	
		1.5	2.0	2.5	3.0	77	70	64	60	72	66	61	57	62	57	53	50	52	49	46	44	35																																	
		2.0	2.5	3.0	4.0	82	76	71	67	76	71	67	63	66	62	59	56	56	53	51	49	38																																	
		2.5	3.0	4.0	5.0	85	80	75	72	79	75	71	68	68	65	62	60	58	55	53	52	40																																	
取付高さ	器具間隔最大限		H m	1.10 H m	1.22 H m	3.0	4.0	5.0	7.0	8.8	8.3	8.0	8.3	8.0	7.8	7.5	7.2	7.0	6.8	6.6	6.1	5.9	5.8	5.7	4.3																														
	横方向 ( A )	縦方向 ( B )				4.0	5.0	7.0	8.8	8.3	8.0	8.3	8.0	7.8	7.5	7.2	7.0	6.8	6.6	6.1	5.9	5.8	5.7	5.4	4.1																														
						5.0	7.0	8.8	8.3	8.5	8.2	8.0	7.8	7.3	7.1	7.0	6.8	6.2	6.1	5.9	5.8	5.4	4.4																																
						7.0	8.8	8.3	8.7	8.5	8.3	8.1	7.5	7.3	7.2	7.1	6.3	6.2	6.1	6.1	6.1	6.1	6.1	4.6																															
						10.0	9.4	9.3	9.1	9.0	8.8	8.7	8.5	8.4	7.6	7.5	7.4	7.3	6.4	6.3	6.3	6.2	4.7																																

