

# 屋内照明器具特性

品番 (品名)	L G W 8 5 0 1 7 F	
光源	LDA7L - G / E / W ×1	810.0 lm
管理番号	K0169054 ( 0 ) DB 1	
BZ分類	BZ7 / 0.7 / BZ6	

器具効率	86%	天井	80%				70%				50%				30%				0%		
	上方光束		26%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		60%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.69	0.6	4.2	3.1	2.4	1.9	3.9	2.9	2.3	1.8	3.4	2.6	2.1	1.7	3.0	2.3	1.9	1.5	1.2	
	中	0.67	0.8	4.9	3.9	3.1	2.6	4.6	3.7	3.0	2.5	4.1	3.3	2.7	2.3	3.6	2.9	2.5	2.1	1.7	
	否	0.63	1.0	5.4	4.4	3.7	3.2	5.1	4.2	3.5	3.0	4.5	3.8	3.2	2.8	4.0	3.4	2.9	2.5	2.0	
			1.25	5.9	5.0	4.3	3.7	5.6	4.7	4.1	3.6	4.9	4.2	3.7	3.3	4.3	3.8	3.3	3.0	2.4	
下方投影面積	c m <sup>2</sup>		1.5	6.3	5.4	4.7	4.2	5.9	5.1	4.5	4.0	5.2	4.6	4.1	3.6	4.6	4.1	3.7	3.3	2.7	
	等価発光面積		c m <sup>2</sup>	2.0	6.8	6.0	5.4	4.8	6.4	5.7	5.1	4.6	5.7	5.1	4.6	4.2	5.0	4.6	4.2	3.9	3.2
取付高さ	器具間隔最大限		2.5	7.1	6.4	5.8	5.3	6.7	6.1	5.6	5.1	6.0	5.5	5.0	4.7	5.3	4.9	4.5	4.2	3.5	
	横方向 (A)	縦方向 (B)	3.0	7.3	6.7	6.2	5.7	6.9	6.4	5.9	5.5	6.2	5.7	5.3	5.0	5.5	5.1	4.8	4.5	3.8	
H m	1.39 H m	1.39 H m	4.0	7.6	7.1	6.7	6.3	7.2	6.8	6.3	6.0	6.5	6.1	5.8	5.5	5.8	5.5	5.2	5.0	4.1	
			5.0	7.8	7.4	7.0	6.6	7.4	7.0	6.7	6.3	6.6	6.3	6.0	5.8	5.9	5.7	5.5	5.2	4.4	
			7.0	8.0	7.7	7.4	7.1	7.6	7.3	7.0	6.8	6.9	6.6	6.4	6.2	6.2	6.0	5.8	5.6	4.7	
			10.0	8.2	7.9	7.7	7.5	7.8	7.6	7.4	7.2	7.1	6.9	6.7	6.5	6.4	6.2	6.1	5.9	5.0	

