

屋内照明器具特性

品番 (品名)	NNCF23235 (JYOUJI _ CEILING)											
光源	LED5000_85_2800 x1 2800.0 lm											
管理番号	K0185376 (1) DB 1											
BZ分類	BZ5											

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	8 %	室指数	照明率 (X0.01)																ZCM		
下方光束	92 %																				
保守率	良 中 否 0.83 0.81 0.77	0.6	55	42	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25		
		0.8	65	53	45	39	63	52	44	39	59	50	43	38	55	47	42	37	34		
		1.0	71	60	52	47	69	59	52	46	65	56	50	45	61	54	48	44	41		
		1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	60	55	51	47		
下方投影面積	c m ²	1.5	81	72	65	59	79	71	64	59	75	68	62	57	70	65	60	56	52		
		2.0	87	79	73	68	85	78	72	67	80	74	69	65	76	71	67	63	59		
取付高さ	器具間隔最大限		2.5	90	84	78	74	88	82	77	73	84	79	74	70	79	75	72	68	64	
	横方向 (A)	縦方向 (B)	3.0	93	87	82	78	91	85	81	77	86	82	78	74	82	78	75	72	68	
1.5m	2 m	1.95 m	4.0	96	92	87	84	94	90	86	82	89	86	83	80	85	82	80	77	73	
2	2.64	2.54	5.0	98	94	91	88	96	92	89	86	91	88	86	83	87	85	83	81	76	
2.5	3.29	3.16	7.0	100	97	95	92	98	95	93	91	94	92	90	88	90	88	86	85	80	
3	3.96	3.79	10.0	102	100	98	96	100	98	96	94	96	94	92	91	92	90	89	88	83	

