

屋内照明器具特性

品番 (品名)	NNCF42235 (J YOUJI _ WALL)														
光源	LED5000_85_3800 ×1 3800.0 lm														
管理番号	K0185575 (1) DR 1														
BZ分類	BZ10/0.9/BZ9														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	50 %	室指数	照明率 (X0.01)																ZCM		
下方光束	50 %																				
保守率	良	0.83	0.6	43	31	23	17	39	28	21	15	32	23	17	13	25	18	13	10	5	
	中	0.81	0.8	52	39	30	24	47	36	28	22	38	29	23	18	30	23	18	14	8	
	否	0.77	1.0	57	45	36	30	52	41	33	27	43	34	28	23	34	27	22	18	10	
			1.25	63	51	43	36	57	47	39	33	47	39	33	28	37	31	26	22	13	
下方投影面積			c m ²	1.5	67	56	48	41	61	52	44	38	50	43	37	32	40	34	30	26	16
等価発光面積			c m ²	2.0	73	63	56	49	67	58	51	46	55	49	43	38	44	39	35	31	20
取付高さ	器具間隔最大限			2.5	77	68	61	55	70	63	57	51	58	53	47	43	47	43	39	35	23
	横方向 (A)	縦方向 (B)		3.0	79	72	65	60	73	66	60	55	61	55	51	47	49	45	42	38	25
1.5m	0	2.12m		4.0	83	77	71	66	76	71	66	61	64	60	56	52	52	49	46	43	29
2	0	2.7		5.0	85	80	75	71	79	74	70	65	66	62	59	56	54	51	49	46	32
2.5	0	3.3		7.0	88	84	80	76	82	78	74	71	69	66	63	60	57	55	52	50	35
3	0	3.91		10.0	90	87	84	81	84	81	78	76	71	69	67	65	59	57	56	54	38

