

屋内照明器具特性

品番 (品名)	NNCF50121J (JYOUJI)	
光源	LED2700_85_820 ×1	820.0 l m
管理番号	K0170340 (1) DR 1	
BZ分類	BZ6/3.5/BZ7	

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	49%	反射率	床	10%				10%				10%				10%				0%			
下方光束	51%		室指数	照明率 (X0.01)																			
保守率	良 中 否 0.81 0.77 0.68	0.6	48	36	28	23	44	33	26	22	37	28	23	19	30	24	19	16	11				
		0.8	56	45	37	31	52	41	34	29	43	35	30	25	35	29	25	22	15				
		1.0	62	51	43	37	57	47	40	35	48	40	35	30	39	33	29	26	18				
		1.25	67	57	49	44	62	53	46	41	52	45	40	35	43	37	33	30	21				
下方投影面積	c m ²	1.5	71	62	54	48	65	57	51	45	55	49	43	39	45	40	36	33	23				
		2.0	76	68	62	56	70	63	57	52	59	54	49	45	49	45	41	38	27				
取付高さ	器具間隔最大限		2.5	80	73	67	61	74	67	62	57	62	57	53	49	51	48	44	29				
	横方向 (A)	縦方向 (B)	3.0	82	76	70	65	76	70	65	61	64	60	56	53	53	50	47	32				
H m	0.00 H m	1.74 H m	4.0	85	80	75	71	79	74	70	66	67	63	60	57	56	53	51	35				
			5.0	87	83	79	75	81	77	73	70	69	66	63	60	57	55	53	51	37			
			7.0	90	86	83	80	84	80	77	75	71	69	67	64	60	58	56	39				
			10.0	92	89	87	84	85	83	81	79	73	71	69	68	61	60	59	42				

