

# 屋内照明器具特性

品番 (品名)	NNCF55130 ( JYOUJI )				
光源	LED5000_85_990 ×1                      990.0 lm				
管理番号	K0170341 ( 1 ) DR 1				
BZ分類	BZ7				

器具効率	100%	天井	80%				70%				50%				30%				0%																	
	上方光束		70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%													
	下方光束	50%	壁	10%				10%				10%				10%				0%																
	50%	室指数																																		
		照明率 ( X0.01 )																								Z	C					M				
保守率	良 中 否	0.81	0.6	47	35	27	22	43	32	25	20	36	27	22	18	29	23	18	15	10																
		0.77	0.8	55	43	35	29	50	40	33	27	42	34	28	24	34	28	23	20	13																
			1.0	61	50	41	35	56	46	39	33	46	39	33	28	38	32	27	24	16																
			0.68	1.25	66	56	48	42	61	51	44	39	51	43	38	33	41	36	31	28	19															
下方投影面積			cm <sup>2</sup>																																	
			cm <sup>2</sup>																																	
取付高さ	器具間隔最大限																																			
	横方向 (A)		縦方向 (B)																																	
1.5m	0.58m	2.41m																																		
2	0.76	3.21																																		
2.5	0.95	4.01																																		
3	1.14	4.81	10.0	92	89	86	84	85	83	80	78	73	71	69	67	61	59	58	57	41																

