

# 屋内照明器具特性

品番 (品名)	NNCF50131 (JYOUJI)															
光源	LED2700_85_1100 x1 1100.0 lm															
管理番号	K0170338 (1) DR1															
BZ分類	BZ6/3.5/BZ7															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	49%	反射率	床	10%				10%				10%				10%				0%
下方光束	51%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.81	0.6	48	36	28	23	44	33	26	22	37	28	23	19	30	24	19	16	11
		0.77	0.8	56	45	37	31	52	41	34	29	43	35	30	25	35	29	25	22	15
			1.0	62	51	43	37	57	47	40	35	48	40	35	30	39	33	29	26	18
		0.68	1.25	67	57	49	44	62	53	46	41	52	45	40	35	43	37	33	30	21
下方投影面積	c m <sup>2</sup>	1.5	71	62	54	48	65	57	51	45	55	49	43	39	45	40	36	33	23	
		2.0	76	68	62	56	70	63	57	52	59	54	49	45	49	45	41	38	27	
取付高さ	器具間隔最大限		2.5	80	73	67	61	74	67	62	57	62	57	53	49	51	48	44	29	
	横方向 (A)	縦方向 (B)	3.0	82	76	70	65	76	70	65	61	64	60	56	53	53	50	47	32	
H m	0.00 H m	1.74 H m	4.0	85	80	75	71	79	74	70	66	67	63	60	57	56	53	51	35	
			5.0	87	83	79	75	81	77	73	70	69	66	63	60	57	55	53	37	
			7.0	90	86	83	80	84	80	77	75	71	69	67	64	60	58	56	39	
			10.0	92	89	87	84	85	83	81	79	73	71	69	68	61	60	59	42	

