

屋内照明器具特性	
品番 (品名)	HH- CB1213AH
光源	LED0_70_5200 ×1 5200.0 lm
管理番号	K0142412 (0) DB 1
BZ分類	BZ5

器具効率		100 % 上方光束 8 % 下方光束 92 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	54	42	34	29	53	41	34	28	49	39	33	28	47	38	32	27	25	
			0.6	0.8	64	52	44	38	62	51	44	38	58	49	42	37	55	47	41	36	33	
			0.56	1.0	71	60	52	46	68	58	51	45	64	56	49	44	61	53	48	43	40	
				1.25	76	66	59	53	74	65	58	52	70	62	56	51	66	59	54	50	46	
下方投影面積 等価発光面積		cm ² cm ²		1.5	81	71	64	58	78	70	63	58	74	67	61	56	70	64	59	55	51	
			2.0	86	78	72	67	84	77	71	66	79	73	68	64	75	70	66	62	58		
取付 高さ	器具間隔最大限			2.5	90	83	77	72	87	81	76	71	83	78	73	69	79	74	70	67	63	
	横方向 (A)		縦方向 (B)	3.0	92	86	81	77	90	84	80	75	85	81	77	73	81	77	74	71	67	
H m	1.29 H m		1.29 H m	4.0	96	91	86	82	93	89	85	81	89	85	82	79	85	81	79	76	71	
				5.0	98	93	90	86	95	91	88	85	91	88	85	82	87	84	82	79	75	
				7.0	100	97	94	91	98	95	92	90	93	91	89	87	89	87	85	84	79	
				10.0	102	99	97	95	100	97	95	93	95	93	92	90	91	90	88	87	82	

