

屋内照明器具特性	
品番 (品名)	HH- CB1 2 8 2 A
光源	LED6200_70_5000 ×1 5000.0 lm
管理番号	K0149853 (0) DB 1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 7 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		6 3 %																				
保守率		良 中 否	0 . 6 3	0 . 6	5 0	3 9	3 1	2 6	4 7	3 6	3 0	2 5	4 1	3 3	2 7	2 3	3 6	2 9	2 4	2 0	1 6	
			0 . 6	0 . 8	5 9	4 8	4 0	3 5	5 6	4 6	3 9	3 3	4 9	4 1	3 5	3 0	4 2	3 6	3 1	2 7	2 2	
			0 . 5 6	1 . 0	6 6	5 5	4 7	4 2	6 2	5 2	4 5	4 0	5 4	4 6	4 1	3 6	4 7	4 1	3 6	3 3	2 6	
				1 . 2 5	7 1	6 2	5 4	4 9	6 7	5 8	5 2	4 6	5 9	5 2	4 6	4 2	5 1	4 6	4 1	3 8	3 1	
下方投影面積		c m ²	1 . 5	7 5	6 6	5 9	5 4	7 1	6 3	5 6	5 1	6 2	5 6	5 1	4 7	5 4	4 9	4 5	4 2	3 4		
			等価発光面積	2 . 0	8 1	7 3	6 7	6 2	7 6	6 9	6 4	5 9	6 7	6 2	5 7	5 3	5 8	5 4	5 1	4 8	3 9	
取付高さ	器具間隔最大限		2 . 5	8 4	7 8	7 2	6 7	7 9	7 3	6 8	6 4	7 0	6 5	6 1	5 8	6 1	5 8	5 5	5 2	4 2		
	横方向 (A) 縦方向 (B)		3 . 0	8 7	8 1	7 6	7 2	8 2	7 6	7 2	6 8	7 2	6 8	6 5	6 1	6 3	6 0	5 7	5 5	4 5		
H m	1 . 3 0 H m	1 . 3 0 H m	4 . 0	9 0	8 5	8 1	7 7	8 5	8 1	7 7	7 4	7 5	7 2	6 9	6 6	6 6	6 3	6 1	5 9	4 8		
			5 . 0	9 2	8 8	8 4	8 1	8 7	8 3	8 0	7 7	7 7	7 4	7 2	6 9	6 8	6 5	6 4	6 2	5 0		
			7 . 0	9 4	9 1	8 8	8 6	8 9	8 6	8 4	8 1	7 9	7 7	7 5	7 3	7 0	6 8	6 7	6 5	5 3		
			1 0 . 0	9 6	9 3	9 1	8 9	9 0	8 9	8 7	8 5	8 1	7 9	7 8	7 6	7 1	7 0	6 9	6 8	5 5		

