

屋内照明器具特性	
品番 (品名)	HH- CB1 2 8 4 AT 3
光源	LED6200_70_5439 ×1 5439.0 lm
管理番号	K0152038 (0) DB 1
BZ分類	BZ6 / 0.7 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		3 2 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		6 8 %																			
保守率		良 中 否	0 . 6 3	0 . 6	5 1	3 9	3 1	2 6	4 8	3 7	3 0	2 5	4 3	3 4	2 8	2 3	3 8	3 0	2 5	2 1	1 7
			0 . 6	0 . 8	6 0	4 9	4 1	3 5	5 7	4 6	3 9	3 4	5 0	4 2	3 6	3 2	4 5	3 8	3 3	2 9	2 4
				1 . 0	6 7	5 6	4 8	4 2	6 3	5 3	4 6	4 1	5 6	4 8	4 2	3 8	4 9	4 3	3 8	3 5	2 9
			0 . 5 6	1 . 2 5	7 2	6 2	5 5	4 9	6 8	5 9	5 3	4 8	6 1	5 4	4 8	4 4	5 4	4 8	4 4	4 0	3 4
下方投影面積		c m ²		1 . 5	7 6	6 7	6 0	5 5	7 2	6 4	5 8	5 3	6 4	5 8	5 3	4 9	5 7	5 2	4 8	4 4	3 7
			等価発光面積	c m ²	2 . 0	8 2	7 4	6 8	6 3	7 8	7 1	6 5	6 0	6 9	6 4	5 9	5 6	6 2	5 8	5 4	5 1
取付 高さ	器具間隔最大限			2 . 5	8 5	7 9	7 3	6 9	8 1	7 5	7 0	6 6	7 3	6 8	6 4	6 0	6 5	6 1	5 8	5 5	4 6
	横方向 (A)		縦方向 (B)	3 . 0	8 8	8 2	7 7	7 3	8 3	7 8	7 4	7 0	7 5	7 1	6 7	6 4	6 7	6 4	6 1	5 8	4 9
H m	1 . 3 1 H m	1 . 3 1 H m		4 . 0	9 1	8 6	8 2	7 9	8 6	8 2	7 9	7 5	7 8	7 5	7 2	6 9	7 0	6 7	6 5	6 3	5 3
				5 . 0	9 3	8 9	8 6	8 2	8 8	8 5	8 2	7 9	8 0	7 7	7 4	7 2	7 1	6 9	6 7	6 6	5 5
				7 . 0	9 5	9 2	9 0	8 7	9 1	8 8	8 6	8 3	8 2	8 0	7 8	7 6	7 4	7 2	7 0	6 9	5 9
				1 0 . 0	9 7	9 5	9 3	9 1	9 2	9 0	8 9	8 7	8 4	8 2	8 1	7 9	7 5	7 4	7 3	7 2	6 1

