

屋内照明器具特性	
品番 (品名)	S L B 5 5 0 1 9
光源	LED3500_70_1355 ×1 1355.0 l m
管理番号	K0195204 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		20 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		80 %	室指数	照明率 (X0.01) ZCM																	
保守率		良	0.69	0.6	51	39	31	25	49	37	30	25	44	35	28	23	40	32	26	22	19
		中	0.67	0.8	61	49	40	34	58	47	39	34	53	43	37	32	48	40	35	30	26
		否	0.63	1.0	67	56	47	41	64	54	46	40	58	50	43	38	53	46	40	36	32
		1.25	73	62	54	48	70	60	53	47	64	56	49	45	58	52	46	42	37		
下方投影面積		cm ²		1.5	77	67	60	54	74	65	58	52	67	60	54	49	62	56	51	47	41
等価発光面積		cm ²		2.0	83	74	68	62	79	72	65	60	73	66	61	57	67	62	57	54	48
取付高さ	器具間隔最大限			2.5	86	79	73	68	83	76	71	66	76	71	66	62	70	66	62	58	52
	横方向 (A)		縦方向 (B)	3.0	89	82	77	72	85	80	75	70	79	74	70	66	72	69	65	62	55
1.5m	2.2 m	1.96 m	4.0	92	87	82	78	89	84	80	76	82	78	75	71	76	73	70	67	60	
2	2.93	2.59	5.0	94	90	86	82	91	87	83	80	84	81	78	75	78	75	73	70	63	
2.5	3.67	3.21	7.0	97	93	90	87	93	90	87	85	87	84	82	80	80	78	76	75	67	
3	4.4	3.85	10.0	99	96	94	92	95	93	91	89	89	87	85	83	82	81	79	78	70	

